



**Electrical specifications**

**Center Frequency:** 942.5 MHz  
**Bandwidth:** 35 MHz  
**VSWR:** 2.0 : 1 min  
**Input / Output Impedance:** 50 Ohms  
**Passband:** 925-960 MHz  
**Passband Insertion Loss:** 4.0 dB max  
**Passband Ripple:** 1.0 dB max  
**Rejection:** 25 dB min at 750.2-785.2 MHz  
**Rejection 2:** 10 dB min at 880-915 MHz  
**Rejection 3:** 20 dB min at 1304.2-1339.2 MHz  
**Rejection 4:** 50 dB min at 1479-1514 MHz  
**Rejection 5:** 50 dB min at 735.4-770.4 MHz  
**Rejection 6:** 60 dB min at 371-406 MHz  
**Rejection 7:** 60 dB min at 545.8-580.8 MHz  
**Rejection 8:** 55 dB min at 1099.8-1134.8 MHz  
**Power Handling:** 3 Watt max

**Mechanical**

**Mounting Method:** SMT  
**Dimensions:** 26mm x 17mm x 7.5mm

**Environmental**

**Operating Temperature:** -20°C to 70°C  
**Storage Temperature:** -50°C to +90°C

**This product is RoHs compliant.**

**Outline Drawing:**

