

TOLERANCE UNLESS OTHERWISE SPECIFIED DO NOT MAKE MANUAL REVISIONS TO MASTER.



| ISSUE NUMBER | |
|--------------|--|
| ORIGINAL | |

(1)





6.10 6.10

NOTES:

MATERIAL: HOUSING: SHELL: CONTACT:

OPERATING TEMPERATURE:

 .X
 ±0.25

 .XX
 ±0.13

 .XXX
 ±0.05

POWER/CO-AX CONTACT RATING:30A (CURRENT)(IF PRESENT)SIGNAL CONTACT CURRENT RATING:5A PER CONTACTSIGNAL CONTACT RESISTANCE:10mΩ MAX.

INSULATOR RESISTANCE: DIELECTRIC WITHSTANDING VOLTAGE: 5000MΩ min.


1000V AC rms

-55°C ~ 125°C

THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, GOLD FLASH PLATED

STEEL, NICKEL PLATED



| | | | | SW REFERENCE NO.: 629 COMBO ASSEMBLY | | | | | | |
|--|--------------------|--|--|--------------------------------------|-----------------|---------|---------|-----------|-------|--|
| | COMBINATION D-SUB | | | | C.B | | DATE: | JAN. 01/2 | 2019 | |
| | | | | CHECKED | : | | DATE: | | | |
| | | EDAC INC TORONTO, ONTARIO CANADA | THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF EDAC INC.,AND SHALL NOT BE REPRODUCED,OR COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION. | SCALE: | (IN C.A.D. 1:1) | | SHEET | 1 0 | = 2 | |
| | | | | DRAWING NUMBER: 629-7W2-250-3N3 | | | | | ISSUE | |
| | YOUR CONNECTION TO | QUALITY & SERVICE | | PART NUM | /BER: 6 | 29-7W2- | 250-3N3 | | 1 | |



THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

