

## Mounting base housing - HSC-LR 5U KIT 2003 - 2201796

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




DIN rail housing, 5U, Lock and Release system, width: 16.1 mm

### Your advantages

- Item is from the ME-IO product range
- Tool-free mounting
- Push-in front connection technology
- Available for up to 30-pos. front connection technology

### Key Commercial Data

Packing unit	10 pc
Minimum order quantity	10 pc
GTIN	 4 046356 933605
GTIN	4046356933605

### Technical data

#### Item properties

Brief article description	Mounting base housing
Type	HSC-LR 5U KIT 2003
Order No.	2201796
Housing type	DIN rail housing
Type	5U
Mounting type	Snap in

#### Dimensions

Width [ w ]	16.1 mm
Height [ h ]	67.95 mm
Depth [ d ]	8.8 mm

# Mounting base housing - HSC-LR 5U KIT 2003 - 2201796

## Technical data

### Material data

Color (RAL)	orange
Flammability rating according to UL 94	V0
Housing material	Polyamide

### Ambient conditions

Ambient temperature (storage/transport)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 100 °C
Ambient temperature (operation)	-40 °C ... 105 °C (depending on power dissipation)
Relative humidity (storage/transport)	80 %

### PCB data

Mounting position	Vertical (horizontal DIN rail)
-------------------	--------------------------------

### Packaging information

Pieces per package	10
Denomination packing units	Pcs.

### Standards and regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Approvals

### Approvals

Approvals

UL Recognized

Ex Approvals

### Approval details

UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	FILE E 240868
---------------	---	---	---------------

Phoenix Contact 2019 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>