

**PROtop  
PRO COM CAN OPEN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 16

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



High-end power supplies must perform efficiently and reliably, even in challenging industrial environments. This requires high power reserves, a long service life and optimal protection against overvoltage, vibration and extreme temperature conditions.

New DCL technology gives PROtop an outstanding dynamic range. This can be used for the reliable triggering of circuit breakers or for powerful motor starts.

**General ordering data**

Type	PRO COM CAN OPEN
Order No.	<a href="#">2467320000</a>
Version	
GTIN (EAN)	4050118482225
Qty.	1 pc(s).

**PROtop  
PRO COM CAN OPEN**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Width	35 mm	Width (inches)	1.378 inch
Height	74.4 mm	Height (inches)	2.929 inch
Depth	33.6 mm	Depth (inches)	1.323 inch
Weight	36 g	Net weight	76 g

**Temperatures**

Operating temperature, max.	70 °C	Operating temperature, min.	-25 °C
Operating temperature	-25 °C...70 °C	Storage temperature	

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
------------	----------------

**General data**

Operating temperature	-25 °C...70 °C	Protection degree	IP20
Weight	36 g		

**System data**

Connection type	2 x RJ45 plug-in connectors	Field bus protocol	CANopen
Interface	PROtop interconnection interface	Module type	plug-on module

**Classifications**

ETIM 6.0	EC001604	eClass 6.2	27-04-90-04
eClass 9.1	27-04-07-92		

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Software	<a href="#">EDS File</a>
----------	--------------------------