

Wideband Load Insensitive Mixer

Rev. V3

Features


- LO 50 TO 5000 MHz
- RF 50 TO 5000 MHz
- IF 50 TO 3000 MHz
- LO Drive +10 dBm (Nominal)
- Insensitive to System Load Mismatch
- High Intercept: +18 dBm

Description

The SM5T is a termination insensitive mixer, designed for use in military, wireless and test equipment applications. The design utilizes Schottky bridge quad diodes, broadband ferrite baluns and internal loads to provide excellent performance without degradation due to external VSWR mismatches.

Environmental screening available to MIL-STD-883, MIL-STD-202 or MIL-DTL-28837, consult factory.

Product Image



Ordering Information

Part Number	Package
SM5T	Surface Mount


Electrical Specifications: $Z_0 = 50 \Omega$, $L_o = +10$ dBm (Downconverter application only)

Parameter	Test Conditions	Units	Typical	Guaranteed	
				+25°C	-40° to 85°C
SSB Conversion Loss (max) & SSB Noise Figure (max)	$f_R = 0.05$ to 1.5 GHz, $f_L = 0.05$ to 1.5 GHz, $f_I = 0.05$ to 1.5 GHz	dB	6.9	8.3	9.0
	$f_R = 1.5$ to 3.0 GHz, $f_L = 1.5$ to 3.0 GHz, $f_I = 0.05$ to 3.0 GHz	dB	7.5	8.8	9.5
	$f_R = 3.0$ to 5.0 GHz, $f_L = 3.0$ to 5.0 GHz, $f_I = 0.05$ to 3.0 GHz	dB	8.5	10.5	11.2
Isolation, L to R (min)	$f_L = 0.05$ to 1.0 GHz	dB	35	25	23
	$f_L = 1.0$ to 5.0 GHz	dB	33	23	21
Isolation, L to I (min)	$f_L = 0.05$ to 1.0 GHz	dB	40	32	30
	$f_L = 1.0$ to 5.0 GHz	dB	35	25	23
Isolation, R to I (min)	$f_R = 0.05$ to 5.0 GHz	dB	32		
1 dB Conversion Comp.	$f_L = +10$ dBm	dBm	+7		
Input IP3	$f_L = 0.05$ to 5.0 GHz, $f_R = 0.05$ to 5.0 GHz, $f_I = 0.05$ to 3.0 GHz	dBm	+18		
VSWR	R-Port $f_R = 0.05$ to 5.0 GHz, L-Port $f_L = 0.05$ to 5.0 GHz, I-Port $f_I = 0.05$ to 3.0 GHz		1.8:1 1.6:1 1.4:1		

Absolute Maximum Ratings

Parameter	Absolute Maximum
Operating Temperature	-54°C to +100°C
Storage Temperature	-65°C to +100°C
Peak Input Power	+20 dBm @ +25°C +17 dBm @ +100°C
Peak Input Current	50 mA DC

Outline Drawing: Surface Mount *



* Dimensions are inches (millimeters) ± 0.015 (0.38) unless otherwise specified.

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.