

208V Corded UPS Backplate Outlet Kit for SU6000RT3U, L6-30R, L6-20R, 5-15/20R

MODEL NUMBER: SUPDM12



Highlights

- Converts Tripp Lite's hardwire SU6000RT3U UPS systems to one with AC plug and outlets
- For use with 208V mains and UPS output voltage configurations
- 10 ft. / 3m AC input power cable with NEMA L6-30P input plug
- 1 L6-30R, 2 L6-20R and 10 5-15/20R output receptacles
- Easy quick-connect wiring installs in minutes

Description

Tripp Lite's SUPDM12 corded backplate kit converts Tripp Lite's hardwire SU6000RT3U UPS system into one with AC plug and outlets. 10 ft./3m input line cord with L6-30P plug enables simple connection to 208V 30A mains power. Includes 1 L6-30R, 2 L6-20R and 10 5-15/20R output receptacles. Easy quick-connect wiring installs in minutes.

VOLTAGE COMPATIBILITY NOTE - SUPDM12 supports SU6000RT3U applications configured for 208V nominal input voltage only (See SUPDM13 for 240V input voltage configurations).

Features

- Converts Tripp Lite's hardwire SU6000RT3U UPS system to one with an AC plug and outlets
- 10 ft./3m AC line cord with L6-30P input plug-in connection
- Includes 1 L6-30R, 2 L6-20R and 10 5-15/20R output receptacles
- Easy quick-connect wiring installs in minutes

Specifications

| OVERVIEW | |
|------------------------|--|
| UPC Code | 037332120861 |
| OUTPUT | |
| Output Receptacles | (10) 5-15/20R; (2) L6-20R; (1) L6-30R |
| Output Nominal Voltage | Simultaneous 208 and 120V output |
| Overload Protection | 120V outlets are protected by 2 separate 20A branch rated circuit breakers |



| INPUT | |
|-------------------------------------|-------------------------|
| Nominal Input Voltage(s) Supported | 208V AC |
| UPS Input Cord Length (ft.) | 10 |
| UPS Input Cord Length (m) | 3.1 |
| Recommended Electrical Service | 30A 208V |
| Input Connection Type | NEMA L6-30P input plug |
| Voltage Compatibility (VAC) | 208 |
| PHYSICAL | |
| Shipping Dimensions (hwd / in.) | 5.00 x 8.80 x 13.70 |
| Shipping Dimensions (hwd / cm) | 12.70 x 22.35 x 34.80 |
| Shipping Weight (lbs.) | 5.60 |
| Shipping Weight (kg) | 2.54 |
| Unit Dimensions (hwd / in.) | 2.5 x 5 x 11 |
| Unit Dimensions (hwd / cm) | 6.4 x 12.7 x 28 |
| Unit Weight (lbs.) | 6 |
| Unit Weight (kg) | 2.72 |
| Material of Construction | Steel |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>