

## VICTORIA-MINI-W

~60° wide beam. Ingress protected version.

### SPECIFICATION:

Dimensions	Ø 180.0 mm
Height	10.8 mm
Ingress protection classes	IP66, IP67
ROHS compliant	yes ⓘ



### MATERIALS:

Component	Type	Material	Colour	Finish
VICTORIA-MINI-W	Multi-lens	PMMA	clear	gloss
VICTORIA-MINI-SEAL	Seal	Silicone		











### ORDERING INFORMATION:

Component	Qty in box	MOQ	MPQ	Box weight (kg)
CS17977_VICTORIA-MINI-W » Box size: 400 x 400 x 275 mm	92	92	4	9.9



See also our general installation guide: [www.ledil.com/installation\\_guide](http://www.ledil.com/installation_guide)



#### OPTICAL RESULTS (MEASURED):

<p><b>CREE</b> LED</p> <p>LED J Series 5050 Round LES</p> <p>FWHM / FWTM 53.0° / 81.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 1.1 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: C18057_VICTORIA-MINI-CLIP</p>		
<p><b>CREE</b> LED</p> <p>LED J Series 5050 Square LES 6V</p> <p>FWHM / FWTM 55.0° / 83.0°</p> <p>Efficiency 93 %</p> <p>Peak intensity 1 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: C18057_VICTORIA-MINI-CLIP</p>		
<p><b>LUMILEDS</b></p> <p>LED LUXEON 5050 Square LES</p> <p>FWHM / FWTM 53.0° / 80.0°</p> <p>Efficiency 91 %</p> <p>Peak intensity 1.1 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components: C18057_VICTORIA-MINI-CLIP</p>		
<p><b>MST</b> Your solutions</p> <p>LED RdLED 150mm 7000lm 8x0 120V VICTORIA-MINI</p> <p>FWHM / FWTM 56.0° / 86.0°</p> <p>Efficiency 91 %</p> <p>Peak intensity 0.9 cd/lm</p> <p>LEDs/each optic 2</p> <p>Light colour White</p> <p>Required components: C18057_VICTORIA-MINI-CLIP</p>		





#### OPTICAL RESULTS (MEASURED):

### SAMSUNG





LED LM28xB Series  
FWHM / FWTM 56.0° / 86.0°  
Efficiency 91 %  
Peak intensity 0.9 cd/lm  
LEDs/each optic 2  
Light colour White  
Required components:  
C18057\_VICTORIA-MINI-CLIP



#### OPTICAL RESULTS (SIMULATED):

<p><b>CREE</b> LED</p> <p>LED J Series 2835            FWHM / FWTM 40.0° / 67.0°            Efficiency 94 %            Peak intensity 1.8 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>LUMILEDS</b></p> <p>LED LUXEON 2835 Line            FWHM / FWTM 37.0° / 66.0°            Efficiency 93 %            Peak intensity 2 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	
<p><b>LUMILEDS</b></p> <p>LED LUXEON 2835 Line            FWHM / FWTM 61.0° / 81.0°            Efficiency 90 %            Peak intensity 0.9 cd/lm            LEDs/each optic 2            Light colour White            Required components:</p>	
<p><b>OSRAM</b>  <small>Opto Semiconductors</small></p> <p>LED Duris E 2835            FWHM / FWTM 37.0° / 66.0°            Efficiency 94 %            Peak intensity 2 cd/lm            LEDs/each optic 1            Light colour White            Required components:</p>	


#### OPTICAL RESULTS (SIMULATED):

<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED Duris S8</p> <p>FWHM / FWTM 60.0° / 81.0°</p> <p>Efficiency 92 %</p> <p>Peak intensity 0.9 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p><b>OSRAM</b> Opto Semiconductors</p> <p>LED OSCONIQ S 5050</p> <p>FWHM / FWTM 58.0° / 80.0°</p> <p>Efficiency 91 %</p> <p>Peak intensity 1 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p><b>SAMSUNG</b></p> <p>LED LM28xB Series</p> <p>FWHM / FWTM 39.0° / 66.0°</p> <p>Efficiency 90 %</p> <p>Peak intensity 1.9 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	
<p><b>SAMSUNG</b></p> <p>LED LM28xB Series</p> <p>FWHM / FWTM 40.0° / 67.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 1.9 cd/lm</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>	


#### OPTICAL RESULTS (SIMULATED):

### SAMSUNG


LED LM301B  
 FWHM / FWTM 39.0° / 66.0°  
 Efficiency 90 %  
 Peak intensity 1.8 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:




SEIOL SEMICONDUCTOR  
 LED SEOUL DC 3528  
 FWHM / FWTM 44.0° / 70.0°  
 Efficiency 94 %  
 Peak intensity 1.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



SEIOL SEMICONDUCTOR  
 LED SEOUL DC 3528  
 FWHM / FWTM 42.0° / 70.0°  
 Efficiency 94 %  
 Peak intensity 1.7 cd/lm  
 LEDs/each optic 1  
 Light colour White  
 Required components:



SEIOL SEMICONDUCTOR  
 LED SEOUL DC 3528  
 FWHM / FWTM 62.0° / 82.0°  
 Efficiency 92 %  
 Peak intensity 0.9 cd/lm  
 LEDs/each optic 2  
 Light colour White  
 Required components:



#### OPTICAL RESULTS (SIMULATED):





#### GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

#### MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

#### PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

#### LEDiL Oy

Joensuunkatu 13  
FI-24240 SALO  
Finland

#### LEDiL Inc.

228 West Page Street  
Suite D  
Sycamore IL 60178  
USA

#### Ledil Optics Technology (Shenzhen) Co., Ltd.

# 405 , Block B  
Casic Motor Building  
Shenzhen 518057  
P.R.CHINA

#### Local sales and technical support

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)

#### Shipping locations

Salo, Finland  
Hong Kong, China

#### Distribution Partners

[www.ledil.com/  
where\\_to\\_buy](http://www.ledil.com/where_to_buy)