


T491A225K025ZT7280

Obsolete

B45196H, Tantalum, MnO2 Tantalum, 2.2 uF, 10%, 25 VDC, SMD, Molded, 3216, Height Max = 1.8 mm



Dimensions		
Footprint	3216	
L	3.2mm +/-0.2mm	
W	1.6mm +/-0.2mm	
Н	1.6mm +/-0.2mm	
S	0.8mm +/-0.3mm	
F	1.2mm +/-0.1mm	
K	1.3mm TYP	

Packaging Specifications	
Packaging	T&R, 330mm
Packaging Quantity	9000

General Information		
Series	B45196H	
Dielectric	MnO2 Tantalum	
Style	SMD Chip	
Description	SMD, Molded	
RoHS	Yes	
Termination	Tin	
AEC-Q200	No	
Notes	Obsolete. Old Part Number [Obsolete] Was B45196H5225K106.	

Specifications	
Capacitance	2.2 uF
Capacitance Tolerance	10%
Voltage DC	25 VDC (85C), 16.75 VDC (125C)
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	6%
Failure Rate	N/A
Leakage Current	0.6 uA

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.