



SIGN	DATE	DESCRIPTION	APPROVER
△			
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

- Material:
- Item (A) Terminal housing: Thermoplastic (UL94V-0)
 - Item (B) Terminal cover: Thermoplastic (UL94V-0)
 - Item (C) Female contact : Copper. Tin plated
 - Item (D) Wire guard : Stainless Steel
 - Item (E) Clamp : Steel Stamping , Zinc plated
 - Item (F) Terminal screw: Zinc plating"-slot type,M5
 - Item (G) With flange screw: Zinc plating"*slot type,M5

- Electrical: cULus
- Voltage rating: 600 V
 - Current rating: 115 A
 - Wire range:
 - Solid wire(AWG): 2-20
 - Stranded wire(AWG): 2-20
 - Torque(Lb-In): 36.5
 - Screw: M5
 - Wire strip length: 19-20mm
 - Withstanding Voltage: 2.2 KV
 - Operating temperature: -40°C to +115°C
 - APPROVAL:

KX xx C 1 x 1 xxxx G

No. OF POLES ————

02: 2 POLES

03: 3 POLES

:

10: 10 POLES

COLOR ————

0: BLACK

5: GREEN (RAL 6018/T)

6: BLUE

8: GREY (RAL 7035/D)

G: Pb<40000ppm

0000: "@" Logo (Standard)

000A: "ANYTEK" Mark

Any special item by customer request. please contact sales department.

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		KX 15.0mm Series (with flange) 2P-10P					
PART NO.		KXxxC1x1xxxxG			DWG NO.		8KX0004
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Runner	Runner			X. ±0.50
			2011.04.25	2010.05.24			UNIT: mm
					SHEET: 01/01		X.XX ±0.10
					REV.: B		X° ±1°

POLE	2	3	4	5	6	7	8	9	10
Dim.L	54.4	69.4	84.4	99.4	114.4	129.4	144.4	159.4	174.4
Dim.P	15.0	30.0	45.0	60.0	75.0	90.0	105.0	120.0	135.0
Tol.	±0.20			±0.35			±0.50		