

## Specification Sheet

Part Number: 156-00444



An all-in-one bundling and fastening solution that saves time and reduces costs.

Foam seal prevents ingress of moisture and debris and prevents vibration.

1-Pc Cable Tie/Arrowhead Mount with Seal, 8.5" Long, 50lb Tensile, PA66HIRHS, Natural, 500/bag

Article Number 156-00444

Type T50ROSAH6MDU

Color Natural (NA)

Quantity Per bag

Product Description The arrowhead design of these ties offers a low insertion force and a high extraction force. The foam rubber seal provides additional protection against moisture and debris. One-piece mounting ties offer a complete solution by simultaneously bundling and mounting cables, wires and hoses.

Short Description 1-Pc Cable Tie/Arrowhead Mount with Seal, 8.5" Long, 50lb Tensile, PA66HIRHS, Natural, 500/bag

Global Part Name T50ROSAH6MDU-PA66HIRHS-NA

Minimum Tensile Strength (Imperial) 50.0

Minimum Tensile Strength (Metric) 225

Length L (Imperial) 8.5

Length L (Metric) 216.0

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Outside Serrated

Width W (Imperial) 0.2

Width W (Metric) 5.0

Bundle Diameter Min (Imperial) 0.06

Bundle Diameter Min (Metric) 1.6

Bundle Diameter Max (Imperial) 2.0

Bundle Diameter Max (Metric) 50.0

Panel Thickness Min (Imperial)	0.03
Panel Thickness Max (Imperial)	0.08
Panel Thickness Min (Metric)	0.8
Panel Thickness Max (Metric)	2.1
Mounting Hole Diameter D (Imperial)	0.248 - 0.252
Mounting Hole Diameter D (Metric)	6.2 - 6.6 mm
Mounting Hole Diameter D Min (Imperial)	0.248
Mounting Hole Diameter D Max (Imperial)	0.252
Mounting Hole Diameter D Max (Metric)	6.6
Disc Diameter (Metric)	16.0
Disc Diameter (Imperial)	0.63
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
UV Resistant (Yes/No)	No

Operating Temperature -40°F to +230°F (-40°C to +110°C)

Reach Compliant (Article 33) Yes

ROHS Compliant Yes

Package Quantity (Imperial) 500

Package Quantity (Metric) 500

Customs Number 3926909988