

Specification Sheet

Part Number: 156-00876



Outside Serrated Cable Tie & Edge Clip, 8.0" Long, EC22, 1–3 mm Panel, 50lb, PA66HS, Black, 500/pkg

| | |
|---------------------|--|
| Article Number | 156-00876 |
| Type | T50ROSEC22 |
| Color | Black (BK) |
| Features & Benefits | <ul style="list-style-type: none">•Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.•Edge Clip provides low insertion force and high extraction force ideal for assembly environments.•Two piece assembly allows the mount to slide along the strap ensuring proper orientation.•Cable tie is outside serrated to reduce bundle chafing. |
| Quantity Per | bag |

Product Description

HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.

Short Description

Outside Serrated Cable Tie & Edge Clip, 8.0" Long, EC22, 1–3 mm Panel, 50lb, PA66HS, Black, 500/pkg

Global Part Name

T50ROSEC22-PA66HS/PA66HIRHS-BK

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

225

Length L (Imperial)

8.0

Length L (Metric)

200

Fixation Method

EdgeClip, sideways, assembled, 2 piece

Identification Plate Position

none

Releasable Closure

No

Variant

Outside Serrated

Width W (Imperial)

0.18

Width W (Metric)

4.6

Bundle Diameter Min (Imperial)

0.20

Bundle Diameter Min (Metric)

1.0

Bundle Diameter Max (Imperial)

2.0

Bundle Diameter Max (Metric)

45.0

| | |
|---------------------------------------|---|
| Thickness T (Imperial) | 0.05 |
| Thickness T (Metric) | 1.3 |
| Height H (Imperial) | 0.05 |
| Height H (Metric) | 1.3 |
| Panel Thickness Min(Imperial) | 0.04 |
| Panel Thickness Max(Imperial) | 0.12 |
| Panel Thickness Min (Metric) | 1.0 |
| Panel Thickness Max (Metric) | 3.0 |
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HIRHS PA66HS |
| Material Cable Tie | Polyamide 6.6 heat stabilized (PA66HS) |
| Flammability | UL 94 HB |
| Operating Temperature (Metric) | -40°F to +221°F (-40°C to +105°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 500 |

Package Quantity (Metric)

500

Customs Number

3926909988

Weight (Metric)

2052