

T498C684K050ZTE5K5

Obsolete

B45196P, Tantalum, MnO2 Tantalum, High Temperature, .68 uF, 10%, 50 VDC, SMD, Molded, High Temperature, N/A, 5.5 Ohms, 6032, Height Max = 2.8mm



General Information

Series	B45196P
Dielectric	MnO2 Tantalum
Style	SMD Chip
Description	SMD, Molded, High Temperature
Features	High Temperature
RoHS	Yes
Termination	Tin
AEC-Q200	No
Notes	Obsolete. Old Part Number [Obsolete] Was B45196P7684K309.

Specifications

Capacitance	.68 uF
Capacitance Tolerance	10%
Voltage DC	50 VDC (85C), 39.85 VDC (125C), 33.5 VDC (150C)
Temperature Range	-55/+150°C
Rated Temperature	85°C
Dissipation Factor	3%
Failure Rate	N/A
Resistance	5.5 Ohms (100kHz)
Leakage Current	0.5 uA

Dimensions

Footprint	6032
L	6mm +/-0.3mm
W	3.2mm +/-0.3mm
H	2.5mm +/-0.3mm
S	1.3mm +/-0.3mm
F	2.2mm +/-0.1mm
K	1.8mm TYP

Packaging Specifications

Packaging	T&R, 178mm
Packaging Quantity	750