

## Coaxial Cable Connector 21\_TNC-50-3-17/133\_N

### Description

Straight cable jack

Interface standards

IEC 60169-17\_MIL-STD-348A/313\_CECC 22200



### Technical Data

#### Electrical Data

Impedance	50 $\Omega$
Interface frequency max.	11 GHz

#### Mechanical Data

Centre contact	crimped
Outer contact	crimped
Weight	0.021 kg

#### Environmental Data

Operating temperature	-65 °C to 165 °C
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant

#### Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Gold Plating (Nickel underplated)
Outer contact	Brass	SUCOPLATE (R) Plating
Body	Brass	SUCOPLATE (R) Plating
Insulator	PFA / PTFE	
Crimp ferrule	Copper	SUCOPLATE (R) Plating

### Related Documents

Outline drawing	DOU-00165883
Assembly instruction	DOC-0000344856

### Ordering Information

Single package	21_TNC-50-3-17/133_NE
----------------	-----------------------

### Additional Information

Suitable cables	ENVIROFLEX_400, RADOX_RF_400
-----------------	------------------------------

### Remarks

Shrinking Tube included