

Power module - FL SWITCH 4800E-P5 - 2891076

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Modular power supply for FL SWITCH 48... managed switches. Wide input voltage range 90 V AC to 264 V AC and 88 V DC to 300 V DC.




Your advantages

- ✓ Network structure according to IEC 61850
- ✓ IEEE 1613



Key Commercial Data

Packing unit	1 pc
GTIN	 4 046356 764407
GTIN	4046356764407

Technical data

Note

Utilization restriction	EMC: class A product, see manufacturer's declaration in the download area
-------------------------	---

Dimensions

Width	151 mm
Height	40 mm
Depth	214 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)

Input data

Nominal input voltage	115 V AC
-----------------------	----------

Power module - FL SWITCH 4800E-P5 - 2891076

Technical data

Input data

	230 V AC
	110 V DC
	250 V DC
Nominal input voltage range	90 V AC ... 264 V AC
	88 V DC ... 300 V DC
AC frequency range	50 Hz ... 60 Hz

General

Net weight	884 g
Degree of protection	IP20

Connection data, input

Connection method	Screw connection
Conductor cross section solid min.	0.8 mm ²
Conductor cross section solid max.	6 mm ²
Conductor cross section flexible min.	0.8 mm ²
Conductor cross section flexible max.	6 mm ²
Conductor cross section AWG min.	18
Conductor cross section AWG max.	10

Environmental Product Compliance

	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 10;
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC / KC

Ex Approvals

Approval details

EAC		RU *- DE.A*30.B.01735
-----	---	--------------------------

Power module - FL SWITCH 4800E-P5 - 2891076

Approvals

KC



<http://eng.kcc.go.kr/user/ehpMain.do>

MSIP-REI-
PCK-2891076

Phoenix Contact 2019 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>