



**Metric table**

Dimensions in: millimeters - inches

d <sub>1</sub> Pin -0.02 Bore H7	l <sub>1</sub>	b <sub>1</sub>	b <sub>2</sub>	d <sub>2</sub> -0.02 -0.1	d <sub>3</sub>	d <sub>4</sub>	d <sub>5</sub>	k	l <sub>2</sub>	l <sub>3</sub> - 0.15	l <sub>4</sub>	l <sub>5</sub> Stroke	Spring load ≈		Axial load
													Initial	End	
6 .24	6 .24	40 1.57	18 .71	10 .39	25 .98	4.3 .17	8.3 .33	30 1.18	37 1.46	2.5 .10	4.5 .18	6 .24	9 N 2.02 lbf	25 N 5.62 lbf	400 N 89.92 lbf
6 .24	14 .55	40 1.57	18 .71	10 .39	25 .98	4.3 .17	8.3 .33	30 1.18	45 1.77	2.5 .10	4.5 .18	6 .24	9 N 2.02 lbf	25 N 5.62 lbf	400 N 89.92 lbf
8 .31	8 .31	46 1.81	20 .79	12 .47	31 1.22	5.3 .21	10.4 .41	34 1.34	44 1.73	2.5 .10	5.5 .22	8 .31	13 N 2.92 lbf	26 N 5.85 lbf	500 N 112 lbf
8 .31	18 .71	46 1.81	20 .79	12 .47	31 1.22	5.3 .21	10.4 .41	34 1.34	54 2.13	2.5 .10	5.5 .22	8 .31	13 N 2.92 lbf	26 N 5.85 lbf	500 N 112 lbf

**Specification**

- Mounting plate  
Zinc die-cast  
Zinc plated, blue passivated finish
- Knob  
Plastic  
Technopolymer (Polyamide PA)  
- Temperature resistant up to 230 °F (110 °C)  
- Black, matte finish  
- Not removable
- **GN 608**  
- Plunger pin  
Steel, hardened  
- Single components  
Steel
- **GN 608.5**  
- Plunger pin  
Stainless steel  
European Standard No. 1.4305 (AISI 303)  
Chemically nickel plated  
- Single components  
Stainless steel
- RoHS compliant

**Information**

GN 608 / GN 608.5 indexing plungers are used in applications that require surface mounting. These series have been expanded with additional plunger pin lengths to widen the application opportunities. Please note that for these longer pin lengths (d<sub>1</sub> = 6 mm, l<sub>1</sub> = 14 mm / d<sub>1</sub> = 8 mm, l<sub>1</sub> = 18 mm), the pin does not fully retract.

**see also...**

- [List of Indexing Plunger Types](#)
- [Locating Bushings GN 412.2 / GN 412.4](#)
- [Locating Bushings with Cone GN 412.3 / GN 412.5](#)
- [Indexing Plungers GN 817.1 \(Lock-Out / Non Lock-Out\)](#)
- [Mini Indexing Plungers GN 822.8 \(Lock-Out / Non Lock-Out\)](#)

How to order (Steel plunger pin)	1	Pin diameter d <sub>1</sub>
	2	Length l <sub>1</sub>
<b>GN 608-8-18</b>		

How to order (Stainless steel plunger pin)	1	Pin diameter d <sub>1</sub>
	2	Length l <sub>1</sub>
<b>GN 608.5-6-14</b>		