Mounting 01-No Mo	<b>Option</b> unting Lugs	Contact Detail 500-Wire Hole .087x.013(2.21x0.33) - Tail LG.=.282 .156 [3.96] Contact Spacing x .140 [3.56] Row Spaci	2(7.16) do not maki	A.D. GENERATED DRAWING E MANUAL REVISIONS TO MAS	TER O	ISSUE NUMBER ORIGINAL
.054	d Slot Accepts (1.37) to .070 (1.78) < P.C. Board					
\ <u>\</u>	0.156[3.96]					
		6.248[158.70] ————————————————————————————————————				
						7.49] d Slot
						0.295[7.49] Card Slot
<b>*</b>					<u> </u>	
0.460[11.68]					0.090 [2.29] of Contact	SECTION A-A
0.460			5 Card Edge Connec 305-078-500-201	tor	ACAD REFERENCE  DRAWN: J.LEE  CHECKED:	NO. 305 ENG MASTER  DATE: SEPT. 21/09  DATE:
See Accompanying Page for:  Mounting Options		YOUR CONNECTION TO	TORONTO, ONTARIO CANADA  ARE THE PRISHALL NOT E OR USED AS MANUFACTUR MANUFACTUR	INGS AND SPECIFICATIONS OPERTY OF EDAC INC.,AND BE REPRODUCED,OR COPIED THE BASIS FOR THE E OR SALE OF APPARATUS TTEN PERMISSION.	DRAWING NUMBER 305 Assemb	SHEET 1 OF 2 ISSUE 1

