

## Specification Sheet

Part Number: 300-73611



Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, 2.0" Supp/1.0" Recov Dia, PO-X, Black, 100ft/reel

Article Number	300-73611
Type	TCN20-50.8/25.4
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Tubing is 2:1, thin wall and self extinguishing providing good resistance to common fluids and solvents.</li><li>• Low shrink temperature gives excellent physical and electrical performance.</li><li>• Available in multiple diameters and lengths offering several options to fit specific needs.</li></ul>
Quantity Per	box

### Product Description

TCN20 Heat Shrink is a general purpose, thin wall tubing used to protect electrical and mechanical wiring. Polyolefin material is self extinguishing and resistant against common fluids and solvents. The low shrink temperature and mechanical strength make this tubing widely used in the electric and electronics industry. Available in a wide range of diameters up to 2.0" (50.8mm) and multiple lengths. TCN20 Heat Shrink is UL224 125 °C 600V VW-1 and RoHS.

**Short Description**

Heat Shrink Tubing, Non-Adh, 2:1 Shrink Ratio, 2.0" Supp/1.0" Recov Dia, PO-X, Black, 100ft/reel

**Global Part Name**

TCN20-50.8/25.4-PO-X-BK

**Length L (Imperial)**

100.0

**Length L (Metric)**

30.5

**Variant**

Thin-Wall

**Nominal Diameter (Imperial)**

2

**Nominal Diameter (Metric)**

50.8

**Wall Thickness WT (Metric)**

1.15

**Material**

Polyolefin, cross-linked (PO-X)

**Material Shortcut**

PO-X

**Flammability**

Self-Extinguishing

**Halogen free**

No

**Operating Temperature (Metric)**

-67°F to +257°F (-55°C to +125°C)

**Reach Complaint(Article 33)**

Yes

**ROHS Complaint**

Yes

**UL Recognized (US)**

Yes

**UL Recognized (US and Canada)**

Yes

**Package Quantity(Imperial)**

100

**Package Quantity (Metric)**

30

**Customs Number**

3926909987