٦	D I	н п	т		0	Φ	Þ	
4		ØS-						4
ω	CHARACTERISTICS		ctor dimension		LAYOUT SHOWN AS	EXAMPLE		3
N	-Standard : Based on MIL-DTL-38999 Series III -Shell Material : Aluminium -Shell Plating : Black Zinc Nickel -Insulator : Thermoplastic -Contacts : Copper Alloy -Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8μm minin -Durability : 500 Mating cycles -Delivered with Souriau contacts and Accessories	Dim ØS Z VV THREAD	Nominal25 Max31 MaxM15x1-6g		SOURIAU shall not be liable for a due to a use of the Products w the Specifications issued by either (professional recommend Coun FR PN: 8D511	which does not comply w of the Parties or by a thin lation, technical notice.) htry Jurisdiction & R Not L	ith rd party & Control List	2
	-Temperature Range : -65°C to +175°C -Salt Spray : 500 hours -Mass : 14.47 g ± 10%			A 18-10-2016 ISS DATE Designed By: TITLE	First Release Latest modification - by Date:		MOD N° OMER DRAWING	
_ _	BASIC SERIES: 8D 5 - 11 SHELL TYPE : Plug with RFI Shielding		ORIENTATION : E CONTACT TYPE : PIN(500 Matings) CONTACT LAYOUT : 11-22	SCALE NA SOURIAU	General linear Tolerances: ± WWW.SOURIAU.	COM	PRDS / PROJECT 859 This document is the property of SOURIAU it must not be reproduced or ommunicated without permission SHEET	1
	H G	F	E	A3	8D5112 C	Z22PE-C B	1/2 A	

	工	۵	г П	m	D	0	
4		Contact Layout 22*					
 ى	Ctc A B C D	4#22D 11-22 X Y 1.905 1.905 1.905 -1.905 -1.905 1.905 -1.905 1.905					
						SOURIAU shall not b due to a use of th the Specifications issu (professional	ne Products w led by either recommend
N					A 18-10-201	PN	Coun FR : 8D511
_					ISS DATE Designed By: TITLE SCALE	Latest modification - b Date:	Alumi General linear
_					NA SOURIAL FORMAT		Tolerances: ± DURIAU.

G

Н

F

Е

A3

D

С

