



Material and Finish

Shell: Steel, nickel plated
 Insulator: PBT thermoplastic with glass-fiber reinforcement, UL94V-0 rated
 Color: Black
 Contact Material: Plug - Brass
 Contact Plating Options:
 Standard: gold flash on mating end, tin on termination end, nickel underplate on entire contact
 15 Option: 15u" gold on mating end, tin on termination end, nickel underplate on entire contact
 30 Option: 30u" gold on mating end, tin on termination end, nickel underplate on entire contact

Electrical Specifications

Rated Current: 1.5A
 Rated Voltage: 30Vac
 Insulation Resistance: more than 1000 megohms at 500V DC
 Contact Resistance: 13 milliohms max.
 Dielectric Withstanding Voltage: 1000V for 1 minute
 Operating Temperature: -55°C to +105°C

Part Number	Contact Area Plating Finish
K86X-ED-15P-BR	Gold Flash (standard)
K86X-ED-15P-BR15	15u" Gold (-15 option)
K86X-ED-15P-BR30	30u" Gold (-30 option)



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	7/19/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	06/30/05
A2	1/17/08	ECO# 07-052	WILL H.	H. MA		
A3	10/2/14	ECO#14-028	H. MA	P. DalCanto		
A4	12/31/17	ECO #17-033	J. Elbanna	C. Furumasu		
						UNITS
						mm

K86X-ED-15P-BR

High Density Vertical Mount D-Sub, RoHS Compliant

15 pin plug, precision formed contacts, boardlocks

