

## V23008A1002A100 Product Details



### V23008A1002A100

(3-1393800-4)

TE Part Number: 3-1393800-4

Active

Add to Part List

### Communications/Signal PC Board Relays

Converted to EU RoHS/ELV Compliant ([Statement of Compliance](#))

#### Product Highlights:

- V23008, V23009/Power Relay 15 Series
- AC Actuating System
- Input Voltage = 230 VAC
- Contact Arrangement = 3 Form C, 3PDT, 3 C/O
- Contact Current Rating = 8 Amps.

[View all Features](#) | [Find Similar Products](#)

### Quick Links

- ▶ [Check Pricing & Availability](#)
- ▶ [Search for Tooling](#)
- ▶ [Product Feature Selector](#)
- ▶ [Contact Us About This Product](#)
- ▶ [Request Samples](#)

NEW!

### Documentation & Additional Information

#### Product Drawings:

- None Available

#### Catalog Pages/Data Sheets:

- None Available

#### Product Specifications:

- None Available

#### Application Specifications:

- None Available

#### Instruction Sheets:

- None Available

#### CAD Files:

- None Available

#### Additional Information:

- [Product Line Information](#)

#### Related Products:

- [Tooling](#)

### Product Features (Please use the Product Drawing for all design activity)

#### Product Type Features:

- Termination Type = Solder/Plug-In Terminals

#### Electrical Characteristics:

- Actuating System = AC
- Input Voltage (VAC) = 230
- Contact Current Rating (Amps.) = 8
- [Coil Resistance \(Ω\)](#) = 2900
- Coil Power, Nominal (VA) = 3.40 – 5.30
- Dielectric Between Coil and Contacts (V rms) = 2500

#### Body Related Features:

- Series = V23008, V23009/Power Relay 15
- Polarized = No

#### Contact Related Features:

- Mounting Options = Socket
- Enclosure = Dust Protected
- [FCC Part 68 Isolation](#) = No
- Approved Standards = None
- Contact Material = Silver
- Approx. Dimensions (L x W x H) (mm [in]) = 53.00 x 46.50 x 61.00 [2.087 x 1.831 x 2.402]
- Compatible Socket = Without
- Contact Type = Single
- Pin Configuration = Industry Standard

#### Configuration Related Features:

- [Contact Arrangement](#) = 3 Form C, 3PDT, 3 C/O
- [Coil Magnetic System](#) = Non Polarized, Monostable
- Coil Suppression Diode = Without

#### Industry Standards:

- [RoHS/ELV Compliance](#) = RoHS compliant, ELV compliant
- [Lead Free Solder Processes](#) = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C
- RoHS/ELV Compliance History = Converted to comply with RoHS directive

#### Other:

- Brand = Axicom