

Power Strips used within the Patient Care Vicinity, may be permanently attached by a means such that it is only removable with the use of a tool. Choose the [PSCLAMP](#) for a safe & secure mounting solution.

## For Patient-Care Vicinity UL 60601-1 Medical-Grade Power Strip with Surge Protection, 4 Hospital-Grade Outlets, 15 ft. Cord

MODEL NUMBER: **SPS415HGULTRA**



Full 60601-1 compliance and agency listing, surge protection, integrated locking safety covers and a 15 ft. cord make this medical-grade power strip ideal for standalone use inside and outside patient-care vicinities.

### Description

The SPS415HGULTRA Medical-Grade Power Strip -- patent #7,375,939 and 8,339,759 -- is designed with full 60601-1 and 60950-1 compliance, making it ideal for standalone use in all patient-care vicinities, therapy rooms, imaging environments, laboratories and administrative areas.

This 120V, 50/60 Hz power strip features a NEMA 5-15P-HG hospital-grade plug and four NEMA 5-15R-HG hospital-grade outlets that include integrated locking safety covers. Plus, 1410 joules of surge suppression prevent dangerous power spikes that can damage connected equipment and destroy data. A 15A resettable circuit breaker also protects your equipment from overloads. An LED indicator tells you power is present and protected from surges (with no ground faults or line/neutral reversals).

Mounting slots and flanges let you install the SPS415HGULTRA on a wide variety of surfaces. The all-metal housing ensures safety and is guaranteed to stand up to demanding environments.

With a switchless design that prevents accidental shutoff and a 15-foot power cord that provides flexibility in placing the power strip, the SPS415HGULTRA is a recommended replacement for all non-compliant power strips.

### Features

**Power Distribution Anywhere in Any Medical Facility** Ideal for stand alone use in all patient-care vicinities, therapy rooms, imaging environments, laboratories and administrative areas 120V, 50/60 Hz

### Highlights

- Approved for standalone use in all patient-care vicinities
- Listed to UL 60601-1 and UL 60950-1 specifications
- 1410 joules of surge suppression
- 4 NEMA 5-15R-HG hospital-grade outlets with locking safety covers
- 15 ft. power cord with NEMA 5-15P-HG hospital-grade plug
- Exclusive, patented anti-microbial coating - 99.9% effective in inhibiting bacteria and viruses

### Package Includes

- SPS415HGULTRA UL 60601-1 Medical-Grade Power Strip
- Owner's manual



power strip complies with UL 60601-1 and UL 60950-1 specifications Automatic site fault detection protects patients and staff Tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 Canadian standards Patent #7,375,939 & 8,339,759

**Versatile Medical-Grade Solution** 4 NEMA 5-15R-HG hospital-grade outlets provide consistent power 15 ft. power cord with NEMA 5-15P-HG plug provides reach to the power source Rugged all-metal housing for long life in demanding environments

**Premium Safety Features** 1410 joules of surge suppression protect against dangerous power spikes Integrated locking outlet safety covers block access to unused outlets Built-in 15A resettable circuit breaker protects against dangerous overloads Switchless design prevents accidental shut-off LED indicates power is present and surge-protected

**Ready to Use Right Out of the Box** Built-in mounting slots and flanges for easy installation on a variety of surfaces

**Exclusive, Patented Antimicrobial Protection** Silver ionic powder coating is 99.9% effective in inhibiting the growth of bacteria like C. diff and MRSA Patented coating helps to reduce the risk of healthcare-acquired infections (HAIs) in hospitals and other medical environments Coating meets the requirements of JIS Z 2801:2000, an international standard for evaluating efficacy in antimicrobial products.

## Specifications

| OVERVIEW                           |                                |
|------------------------------------|--------------------------------|
| UPC Code                           | 037332159236                   |
| OUTPUT                             |                                |
| Frequency Compatibility            | 60 Hz                          |
| Output (Watts)                     | 1800                           |
| Output Receptacles                 | (4) 5-15R-HG                   |
| Circuit Breaker (amps)             | 15                             |
| Overload Protection                | 15A resettable circuit breaker |
| Outlet Orientation                 | Single row of 4                |
| Right-Angle Outlets                | No                             |
| INPUT                              |                                |
| Nominal Input Voltage(s) Supported | 120V AC                        |
| Recommended Electrical Service     | 15A 120V                       |
| Voltage Compatibility (VAC)        | 120                            |
| Maximum Surge Amps                 | 60000                          |
| Input Plug Type                    | NEMA 5-15P-HG                  |
| Input Cord Length (ft.)            | 15                             |
| Right-Angle Plug                   | No                             |
| Input Cord Length (m)              | 4.57                           |
| Integrated Cord Clip               | No                             |
| USER INTERFACE, ALERTS & CONTROLS  |                                |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

|                                     |  |
|-------------------------------------|--|
| Diagnostic LED(s)                   | Yes  |
| LED Indicators                      | Proper wiring and surge protection working   |
| <b>SURGE / NOISE SUPPRESSION</b>    |  |
| AC Suppression Joule Rating         | 1410   |
| Auto Shut-Off                       | No   |
| <b>DATALINE SURGE SUPPRESSION</b>   |  |
| Telephone/DSL Protection            | No   |
| Cable (Coax) Protection             | No   |
| Network (Ethernet) Protection       | No   |
| <b>PHYSICAL</b>                     |  |
| Shipping Dimensions (hwd / in.)     | 14.17 x 5.98 x 2.17  |
| Shipping Dimensions (hwd / cm)      | 35.99 x 15.19 x 5.51   |
| Shipping Weight (lbs.)              | 3.51   |
| Shipping Weight (kg)                | 1.59   |
| Unit Dimensions (hwd / in.)         | 1.5 x 13.75 x 2.5  |
| Unit Dimensions (hwd / cm)          | 3.8 x 34.9 x 6.4   |
| Unit Weight (lbs.)                  | 3.20   |
| Unit Weight (kg)                    | 1.45   |
| Material of Construction            | Metal  |
| Integrated Keyhole Mounting Slots   | Yes (Includes flanges)   |
| Receptacle Color                    | White  |
| Color (AC Line Cord)                | White  |
| Color                               | White  |
| Anti-Microbial Protected            | Yes  |
| <b>CERTIFICATIONS</b>               |  |
| Approvals                           | TUV tested to UL 60601-1 and UL 60950-1 (USA); TUV tested to CAN/CSA-C22.2 No. 601.1-M90 and 60950-1-03 (Canada) |
| Patented                            | Patent# 7,375,939; Patent# 8,339,759   |
| <b>WARRANTY</b>                     |  |
| Product Warranty Period (Worldwide) | Lifetime limited warranty  |

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice.



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>