



C114C221J1G5CA LDD Comm COG, Ceramic, 220 pF, 5%, 100 VDC, COG

LDD Comm COG

**General Information** 

Series





RoHSNoProp 65A WARNING: Cancer and reproductive harm -<br/>http://www.p65warnings.ca.gov.SCIP<br/>Numberf30e2214-6f19-489b-928a-4aa9281a81a7TerminationLead (SnPb)AEC-Q200NoNotesLead Length Shown Is For Parts Supplied In Bulk, See<br/>Packaging Specifications For Lead Lengths When Not<br/>Provided In Bulk.

Specifications	
Capacitance	220 pF
Capacitance Tolerance	5%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+125°C
Temperature Coefficient	COG
Dissipation Factor	0.1% 1 mHz 25C
Insulation Resistance	4.545 GOhms

Click here for the 3D model.

Dimensions	
D	2.29mm +/-0.254mm
L	4.06mm +/-0.254mm
LL	38.1mm MIN
F	0.51mm -0.08mm

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	200

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.