



Description		Article No.	Material
Housing	M4 housing , white	3005001022	PBT GF reinforced
Potting compound	Polyurethane		
Magnet	Round magnet	4003004003	AlNiCo 500 35/5
	Min.	Typ.	Max.
Magnetic moment (MS150)	19,8	22,2	
Operating temperature	-20		80
Remarks	magnetization axial		
Protection class	N/A		
Mounting:	screws M3 ISO 1207, slice ISO 7089		
max. Torque	0,5	Nm	

Application					Tolerance DIN ISO 2768-m	Surface	Scale: 2:1	Weight:
					created: 13.12.2010	wkovacs	<b>MAGNET M04</b>	
				checked: 22.12.2017	mreizner			
				Sheet size: A4				
				dimensions in: mm				
					<b>StandexMeder Electronics GmbH</b> Robert-Bosch-Str.4 78224 Singen Tel.:+49(0)7731/8399-0 Fax:+49(0)7731/8399-30		Art.Nr./DrawingNr. 2500000004	
01		issued in swx, previous versions archived in Navision	21.12.2017	w.k.			Tool Nr.	<small>PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF StandexMeder Electronics GmbH. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF StandexMeder Electronics GmbH IS PROHIBITED.</small>
Rev.	state	change	date	name			<a href="http://www.standexmeder.com">www.standexmeder.com</a>	of 1