



Electronic Test:
 1.100% Test,(Open,Short,Miss Wire)
 2.Contact Resistance:5 ohm max.
 3.Insulation Resistance:10M ohm min.
 4.Hi-Pot:300V DC/10ms

PIN ASSIGNMENT		
P1		P2
1	BLACK	
2	BROWN	
3	RED	
4	ORANGE	
5	YELLOW	
6	GREEN	
7	BLUE	
8	PURPLE	
9	GRAY	
10	WHITE	
11	PINK	
12	LIGHT/GREEN	
13	RED/BLACK	
14	ORANGE/BLACK	
15	YELLOW/BLACK	
16	GREEN/BLACK	
17	BLUE/BLACK	
18	PURPLE/BLACK	
19	WHITE/BLACK	
20	RED/WHITE	
21	ORANGE/WHITE	
22	GREEN/WHITE	
23	BLUE/WHITE	
24	PURPLE/WHITE	
25	BROWN/WHITE	
SHELL		DRAIN

NO	NAMF	O'TY	SPFCIFICATION
⑤	TUBE	1	HEAT SHRINK TUBE BLACK OD1.5*20MM
④	SCREW	2	#4-40UNC TYPE L=30mm,NICKEL PLATED,MOLD:BEIGE(IV-29) ABS
③	IN JACKET	9g	CLEAR LD-PE (Mould NO.:NM-33)
	OUT JACKET	30g	BEIGE(IV-29) 40P PVC(Mould NO.WM-017)
②	CONN	1	DB 25P MALE SODER TYPE PIN G/F SHELL NI-PLATED INSULATOR COLOR:BLUE
①	CABLE	1	NOUL 28AWG*25C+D+AL/MY OD6.5mm JACKET BEIGE(IV-29) L=1000±10MM

RoHS compliant
Unit: mm

Scale	Free				Date	Name
TOLERANCE					Drawn	11.09.2017 Winnie
.x	±0.50				Approved	11.09.2017 Winnie
.xx	±0.30					
DIM	TOL					
		①	Drawn	11.09.2017	Winnie	
Angle	±2°	ld.	Modification	Date	Name	



Customer-No.	
ASSMANN WSW-No. A-DSUB-05-42-28-100	
Drawing-No.	rev00
ASS 8071 CA	Sheet 1/2
Replace	