

SUMMARY

Wires

Low voltage 2



Image is for illustrative purpose only

Series 5K
Termination type Male solder
IP rating 68 when mated
AWG wire size 16.00 - 8.00
Cable Ø 12.60 - 13.50 mm
Status active
Matching parts [EGG.5K.302.CLL](#)

Download

[Request a quote](#)
[Eplan](#)
[Catalog](#)

TECHNICAL DETAILS

Mechanics

Shell Style/Model FG*: Straight plug, cable collet
Keying 1 key (alpha=0, plug: male contacts, receptacle: female contacts)
Housing Material Brass (chrome plated [SAE AMS 2460]) shell, collet nut and latch sleeve, nickel plated [SAE AMS QQ N 290] brass mid pieces
Weight 429.64 g

Performance

Configuration 5K.302 : 2 Low Voltage
Insulator L: PEEK (UL 94 / V-0/1.5)
Rated Current 50 Amps

Specifications


Contact Type: Solder
Contact Dia.: 6 mm (0.236in)
Bucket Dia.: 5.2 mm (0.205in)
Max. Solid Conductor: 10 mm² (AWG 8)
Max. Stranded Conductor: 10 mm² (AWG 8)
R (max): 1.2 mOhm
Vtest (contact-shell): 2950 V (AC), 4170 V (DC)
Vtest (contact-contact): 3600 V (AC), 5090 V (DC)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Others

Endurance (Shell): 5000 mating cycles
Temp (min / max): -55°C / +200°C
Humidity (max): <=95% [at 60 deg C / 140 F]
Vibration: 15 g [10 Hz - 2000 Hz]
Shock Resistance: 100 g [6 ms]
Climatical Category: 50/175/21
Shielding (min): 95 dB (10 MHz)
Shielding (min): 80 dB (1 GHz)
Salt Spray Corrosion: >1000 hr

DRAWINGS



Dimensions

	A	L	M	S2
mm.	38	92	67	30
in.	1,50	3,62	2,64	1,18

RECOMMENDED BY LEMO

Tools

Caps: [BFG.5K.100.NAS](#)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.