

Product data sheet

Characteristics

NSYEBCP27628

Power distribution block, Linergy, enclosed, 760A CU, 600 V, 2 line side lug, 8 load side lug, CU lug, panel mount



Main

Range of Product	NSYEB
Product or Component Type	Power Distribution Block

Complementary

[Ue] rated operational voltage	600 V AC/DC
Line Rated Current	760 A copper
Mounting Support	Panel
Fixing mode	By screws 1/4 inch
Electrical connection	Tin plated copper lugs
Number of terminals	8 load 2 line
Number of cables	Line 2, AWG 4...500 kcmil, copper Load 8, AWG 14...AWG 2/0, copper
Short-circuit current	100 kA
Material	Thermoplastic block
Colour of enclosure	Grey
Wire stripping length	Line 1.38 in (35.05 mm) Load 0.88 in (22.35 mm) top Load 1.38 in (35.05 mm) bottom
Connections - terminals	Load lug 40 lbf.in (4.52 N.m) AWG 8 copper Load lug 35 lbf.in (3.95 N.m) AWG 14...AWG 10 copper Line lug 375 lbf.in (42.37 N.m) AWG 4...500 kcmil copper Load lug 120 lbf.in (13.56 N.m) AWG 6...AWG 2/0 copper
Height	4.63 in (117.60 mm)
Tightening torque	Load 40 lb.in, AWG 8, copper Load 35 lb.in, AWG 14...AWG 10, copper Line 375 lb.in, AWG 4...500 kcmil, copper Load 120 lb.in, AWG 6...AWG 2/0, copper
Width	2.61 in (66.29 mm)
Depth	3.35 in (85.09 mm)
Product compatibility	NSYEBP20 AWG 2/0) NSYEBP500 500 kcmil)

Environment

Product Certifications	CSA file 70361 class 6228 01 UL listed file E323110 CCN QPQS CE
Dielectric strength	1000 V 0.37 in ² (240 mm ²) IEC 60947-7-1
Ambient Air Temperature for Operation	-40...257 °F (-40...125 °C)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

Category	21713-IEC ENCLOSED POWER DISTR BLOCKS
Discount Schedule	CP1
GTIN	785901673927
Nbr. of units in pkg.	1
Package weight(Lbs)	29.76 oz (843.682 g)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.50 in (8.89 cm)
Package 1 width	2.70 in (6.858 cm)
Package 1 Length	4.80 in (12.192 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free product