REV.	ECN NO.	DATE	SIGN	DESCRIPTION
A		2022-01-18	Allen Pan	Rev.01 To Rev.A









SLKC-XXFMMM-GCP-CXX

XX:No. Of Pin

XX:01~15Meters
01:01Meter
02:02Meters
:
:
15:15Meters

Note:
* RoHS Compliant
* QC Important Dimension
* Waterproof Rate: IPX7, Mated
* Connector
  Housing: Thermoplastic, Black
  Pin: Copper Alloy, Gold Plated
  Shell: Metal
  Outer Mold: Thermoplastic, Black
* Cable: IEC61156-12, 26#*1P+AL/MY+B, OD=3.8mm,
  PUR Jacket, Green
* Cable Length Tolerance: 1M: +50/-0 mm
  1M < L ≦ 3M: +100/-0 mm
  3M < L ≦ 5M: +150/-0 mm
  5M < L ≦ 10M: ±100 mm
  10M < L ≦ 15M: ±200 mm



Pin#	Wire	
2	White	白
1	Blue	藍

Pin Assignments
Front View

UNIT:mm

TOLERANCE
±0.5mm

TITLE: FLOS, LK-PLUS, SZ 1, S02P, OM M S/T M, MOLDING, IKEY 0

SCALE	SIZE	SHEET
1:1	A4	1 OF 1

REV. A | WC-REV. A.1 | QC:Inspection item

Amphenol LTW
安費諾亮泰企業股份有限公司

ITEM NO	DRAWN BY	DATE
	Allen Pan	2022-01-18
DWG NO: SLKC-XXFMMM-GCP-CXX	CHECKED BY: Sam Ho	DATE: 2022-01-18
CUSTOMER: ALTW	APPROVED BY: Fred Lee	DATE: 2022-01-18

THIS DOCUMENT IS SUBJECT TO CHANGE WITHOUT NOTICE. IT IS CONFIDENTIAL AND A PROPERTY OF Amphenol LTW. DISCLOSURE TO THIRD PARTY HAS TO BE AUTHORIZED BY Amphenol LTW.