

24-Port 1U Rack-Mount STP Shielded Cat6 /Cat5 Feedthrough Patch Panel, RJ45 Ethernet, TAA

MODEL NUMBER: N254-024-SH



Highlights

- Shielded Cat6 RJ45 Jacks on both sides of the panel
- Installs easily in 19" racks or wall-mounts
- Cable management bar keeps patch cables well-ordered
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- Qualified to IEEE 802.3bt Type 4 PoE for up to 100W of power delivery

Package Includes

- 24-Port Shielded Cat6 Feed-Through 1U Patch Panel
- Detachable Cable Management Bracket

Description

Tripp Lite's 24-Port Shielded Cat6 Feed-Through patch panel provides patching without punching down bulk wire to the back of the panel. Fully meets or exceeds Cat6 specifications - works with USOC, T568A, and T568B wiring. 19" width mounts easily in 2-Post Relay Rack, or a Wall-Mount Hinged Rack. Detachable cable management bar keeps patch cables neat and tidy on the back of the panel. Easy screw down strain relief eliminates the need for cable ties. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases. IEC 60512-99-001 Compliant PoE Certificate Number: 2018-773 STP Cat6 Patch Cord (Requires PoE cable if used in PoE setting)

Features

- Heavy duty 14ga steel construction
- Fully shielded RJ45 / RJ45 Coupler jacks
- Meets or exceeds Cat6 specifications
- Easy patching with Shielded Cat6 patch cable
- Includes cable management bar
- Rackmountable - 19"W x 1.75"H (1U)
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

| OVERVIEW | |
|--------------|---------------|
| UPC Code | 037332171122 |
| Product Type | Feed-Through |
| Technology | Cat5/5e; Cat6 |

| PHYSICAL | |
|-------------------------------------|--|
| Color | Black |
| Shipping Dimensions (hwd / in.) | 2.80 x 19.70 x 4.60 |
| Shipping Dimensions (hwd / cm) | 7.11 x 50.04 x 11.68 |
| Shipping Weight (lbs.) | 2.50 |
| Shipping Weight (kg) | 1.13 |
| Unit Dimensions (hwd / in.) | 1.700 x 19.000 x 1.250 |
| CONNECTIONS | |
| Number of Ports | 24 |
| PoE Power Budget (Watts) | 30 |
| Side A - Connector 1 | RJ45 (FEMALE) |
| Side B - Connector 1 | RJ45 (FEMALE) |
| PoE Type | Type 4 High-Power (100W, IEEE 802.3bt) |
| STANDARDS & COMPLIANCE | |
| Product Compliance | Trade Agreements Act (TAA) |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |