

LTMG402

PRODUCT OVERVIEW

The 4-cable LTMG402 contains elements for two Cellular, one WiFi, and one GNSS antenna. This provides MIMO (multiple-input-multiple-output) coverage for Global LTE Cellular. This antenna is ideal for fleet management systems that combine GNSS with a broadband LTE MIMO modem. GNSS operates on GPS, Galileo, Glonass, QZSS or Beidou.

Specify LTM for units with GPS and LTMG for units with GPS/GLONASS.

Specify MLTMG or MLTM for Mag Mounted units.

Specify CLTM or CLTMG for Ceiling Mounted units.

Visit our eStore to customize an Antenna Online.


Electrical Specifications		
Frequency & Gain	LTE Cables 1 & 2	694 - 960 MHz, 3 dBi 1710 - 3700 MHz, 4 dBi
	WiFi Cable 3	2.4-2.5 & 4.9-6.0 GHz, 5 dBi
	GNSS Cable 4	1561, 1575, & 1602 MHz, LNA 26 dB, 5 dBi (RHCP)
VSWR	< 2:1 VSWR over range	
Impedance	50 Ohm Nominal	
Power Rating	10 Watts	
GNSS	Applier Gain	26 dB
	Amplifier Bias Voltage	3 to 5 VDC
	Noise Figure	2.0 dB max, 1.5 dB typical
	Current	20 mA max, 10 mA typical

Mechanical Specifications	
Radome Material & Color	ASA UV-Inhibitive Plastic, Available in Black or White
Radome Dimension	5.5" (13.9 cm) in diameter 2.38" (6.0 cm) in height
Standard Connectors	SMA Plugs (Male) for LTE & GNSS Rev Pol SMA for WiFi Connection
Cables 1 - 3	Separate LL-195, 15 ft (4.5m)
GNSS Cable 4	RG-174, 15 ft (4.5 m)
Operating Temperature	-40° to +80° C
Mounting	7/8" (22.2 mm) Dia. Feed Through 3/4" (19 mm) Long Thread for Up to 1/2" (12.7 mm) Thick Surface
Shock & Vibration	IEEE1478, EN61373, MIL-810G, TIA 329.2-C
Water Ingress	IP 67 When Properly Mounted



MULTI-BAND ANTENNA

L T M G 4 0 2 - 3 C 3 C 3 J 2 C - W H T - 1 8 0



HIGHLIGHTS:

- Multiband Surface Mount: 2x LTE, 2x WiFi, & 1x GNSS
- Covers 694 - 3700 MHz
- High Performance; High Gain
- Made-in-the-USA & UK

RELATED MODELS:

- LLPG402 (Lower Profile)
- MXFG402 (Same Freq, MaxFin Design)
- LTMG408 (Wider Coverage on 5G Sub-6)
- CLTM402 (Ceiling Mount Model)
- MLTMG402 (Mag Mount Model)
- LTM402 (GPS Model)

COMMON APPLICATIONS:

- Vehicle Fleet Management
- Multiband Modems
- Public Transportation



US Headquarters +1.847.671.6690
US/CA Toll Free +1.800.648.2800
European Facility +44.1543.459555

www.MobileMark.com