



TBR - 03 - **200** - **XX** - **XX** - **LF**  
(A) (B) (C) (D)

- A. Pitch  
- 200= .200(5.08) cl
- B. No. of Positions  
- 02-24
- C. Color  
- GR= Green (Standard)  
- BK= Black  
- BL= Blue  
- WH= White  
- GY= Grey  
- OR= Orange  
- YW= Yellow  
- RD= Red  
- BR= Brown
- D. Lead Free  
Specifications:  
Current Rating: 10 Ampere  
Voltage Rating: AC 300V  
Wire Range: 12-26 AWG  
Insulation Resistance: DC 500V 1000M ohms  
Dielectric Withstanding Voltage: AC 2500V/1 minute  
Operation Temperature: -33°C to +105°C  
Max Torque: 3.47 lb-in (4.0kgf.cm)  
Strip Length: .236-.315 (6-8mm)

- Materials:  
1. Body: PA66 (Nylon), UL94 V-0  
2. Screw: M3.0, C1018 Steel, Zinc Plated  
3. Terminal: Brass, Tin Plated  
4. Contact: Brass, Nickel Plated

Tails may be clipped to achieve specific dimensions.  
Products cut to specific sizes are uncancellable/ nonreturnable.  
Parts are subject to change without notice.



PROPRIETARY AND CONFIDENTIAL  
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Major League Electronics. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Major League Electronics IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DRAWN	EOW	04/18/14	
CHECKED	GWE	04/18/14	
ENG APPR.			
MFG APPR.			
INTERPRET GEOMETRIC TOLERANCING PER:		ADDRESS:	
MATERIAL		2533 Centennial Blvd. Jeffersonville, IN 47130	
NEXT ASSY USED ON		Phone: 812-670-4174	
APPLICATION		Fax: 812-670-4175	
DO NOT SCALE DRAWING		E-Mail: mle@mllectronics.com	
TITLE: TBR-03-200 Series			
SIZE	DWG. NO.	REV	
C		A	
SCALE 8:1			SHEET 1 OF 1