

## Specification Sheet

Part Number: 111-85519



1-Piece Cable Tie/Arrowhead Mount with Wings, 4"L, 18lb, 0.18 - 0.19" Mtg Hole, PA66HS, Natural, 100/bag

Article Number	111-85519
Type	T18RSF
Color	Natural (NA)
Features & Benefits	<ul style="list-style-type: none"><li>•Two piece assembly allows the mount to slide along the strap ensuring proper orientation.</li><li>•Arrowhead style mount provides low insertion and high extraction force.</li><li>•Arrowhead disc protects against dirt and other impurities.</li></ul>
Quantity Per	bag

### Product Description

Wing design helps stabilize the tie in high vibration applications. One-piece mounting ties offer a complete solution by both bundling cable and simultaneously providing a mounting solution. HellermannTyton's one-piece mounting ties offer the ideal combination of high specification materials and superior design to suit the mounting and bundling needs of complex applications.

**Short Description**

1-Piece Cable Tie/Arrowhead Mount with Wings, 4"L, 18lb, 0.18 - 0.19" Mtg Hole, PA66HS, Natural, 100/bag

**Global Part Name**

T18RSF-PA66HS-NA

**Minimum Tensile Strength (Imperial)**

18.0

**Minimum Tensile Strength (Metric)**

80

**Length L (Imperial)**

4.0

**Length L (Metric)**

100

**Fixation Method**

Arrowhead

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.1

**Width W (Metric)**

2.5

**Bundle Diameter Min (Imperial)**

0.06

**Bundle Diameter Min (Metric)**

1.5

**Bundle Diameter Max (Imperial)**

0.6

<b>Bundle Diameter Max (Metric)</b>	16.0
<b>Thickness T (Imperial)</b>	0.039
<b>Thickness T (Metric)</b>	1.0
<b>Panel Thickness Min(Imperial)</b>	0.031
<b>Panel Thickness Max(Imperial)</b>	0.12
<b>Panel Thickness Min (Metric)</b>	0.8
<b>Panel Thickness Max (Metric)</b>	3.0
<b>Mounting Hole Diameter D (Imperial)</b>	0.18 - 0.19
<b>Mounting Hole Diameter D (Metric)</b>	4.6 - 4.8 mm
<b>Mounting Hole Diameter D Min (Imperial)</b>	0.177
<b>Mounting Hole Diameter D Max (Imperial)</b>	0.19
<b>Mounting Hole Diameter D Max (Metric)</b>	4.85
<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Material Cable Tie</b>	Polyamide 6, heat stabilized (PA6HS)
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)

<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	100
<b>Package Quantity (Metric)</b>	100
<b>Customs Number</b>	3926909988
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	0.3