



Click [here](#) for the 3D model.

| Dimensions | |
|------------|---------------------|
| D | 8mm +/-0.5mm |
| L | 6.2mm +/-0.3mm |
| W | 0.65mm +/-0.1mm |
| F | 0.3mm MAX |
| A | 8.3mm +/-0.2mm |
| B | 8.3mm +/-0.2mm |
| C | 9.5mm MAX |
| E | 3.4mm +/-0.2mm |
| G | 0.35mm +0.15/-0.2mm |
| P | 2.2mm +/-0.2mm |

| Packaging Specifications | |
|--------------------------|------------|
| Packaging | T&R, 380mm |
| Packaging Quantity | 1000 |

| General Information | |
|---------------------|--------------------------------------|
| Series | EDK |
| Dielectric | Aluminum Electrolytic |
| Style | SMD Can |
| Description | Surface Mount, Aluminum Electrolytic |
| RoHS | Yes |
| Lead | V-Chip |
| AEC-Q200 | No |

| Specifications | |
|-------------------------|--|
| Capacitance | 330 uF |
| Capacitance Tolerance | 20% |
| Voltage DC | 6.3 VDC, 8 VDC (Surge) |
| Temperature Range | -40/+85°C |
| Rated Temperature | 85°C |
| Life | 2000 Hrs |
| Dissipation Factor | 35% |
| Ripple Current | 300 mAmps (120Hz), 408 mAmps (120Hz 50C) |
| Leakage Current | 21 uA (2min 20°C) |
| Impedance Ratio at -25C | 4 |
| Impedance Ratio at -40C | 8 |
| High Temperature Solder | Yes |