

H G F E D C B A



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

**CHARACTERISTICS**

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Without Plating
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered with Souriau contacts and Accessories
- Temperature Range : -65°C to +175°C
- Salt Spray : 2000 hours
- Mass : 31.3 g ± 10%

| Connector dimension |          |
|---------------------|----------|
| Dim                 | Nominal  |
| ØS                  | 35.7 Max |
| Z                   | 31 Max   |
| VV THREAD           | M25x1-6g |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D517X75PC**

|              |            |                          |                         |
|--------------|------------|--------------------------|-------------------------|
| A            | 18-10-2016 | First Release            |                         |
| ISS          | DATE       | Latest modification - by | MOD N°                  |
| Designed By: |            | Date:                    | <b>CUSTOMER DRAWING</b> |

|              |                                 |  |  |
|--------------|---------------------------------|--|--|
| <b>TITLE</b> | <b>Composite Plug 8D series</b> |  |  |
|--------------|---------------------------------|--|--|

|       |  |                            |                 |
|-------|--|----------------------------|-----------------|
| SCALE |  | General linear Tolerances: | NPRDS / PROJECT |
| NA    |  | ±--                        | <b>859</b>      |

|                |                        |   |
|----------------|------------------------|---|
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b> | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
|----------------|------------------------|---|


|           |                                    |            |
|-----------|------------------------------------|------------|
| FORMAT    | <b>SOURIAU DRG N° 8D517X75PC-C</b> | SHEET      |
| <b>A3</b> |                                    | <b>1/2</b> |

|                |                         |                 |   |    |   |    |   |   |                  |                  |
|----------------|-------------------------|-----------------|---|----|---|----|---|---|------------------|------------------|
| BASIC SERIES:  | 8D                      | 5               | - | 17 | X | 75 | P | C | ORIENTATION : C  |                  |
| SHELL TYPE :   | Plug with RFI Shielding |                 |   |    |   |    |   |   |                  |                  |
| CONTACT TYPE : | Standard Crimp Contact  |                 |   |    |   |    |   |   |                  |                  |
| SHELL SIZE :   | 17                      |                 |   |    |   |    |   |   |                  |                  |
| PLATING :      | X =                     | Without Plating |   |    |   |    |   |   | CONTACT TYPE :   | PIN(500 Matings) |
|                |                         |                 |   |    |   |    |   |   | CONTACT LAYOUT : | 17-75            |

H G F E D C B A

Contact Layout

**75**



2#8 Triax

| 17-75 |   |       |
|-------|---|-------|
| Ctc   | X | Y     |
| A     | 0 | 4.75  |
| B     | 0 | -4.75 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR      | Not Listed                  |

**PN: 8D517X75PC**

|                |                                    |                            |   |
|----------------|------------------------------------|----------------------------|---|
| A              | 18-10-2016                         | First Release              |   |
| ISS            | DATE                               | Latest modification - by   | MOD N°  |
| Designed By:   |                                    | Date:                      | <b>CUSTOMER DRAWING</b>   |
| <b>TITLE</b>   | <b>Composite Plug 8D series</b>    |                            |   |
| SCALE          |                                    | General linear Tolerances: | NPRDS / PROJECT   |
| NA             |                                    | ±--                        | <b>859</b>  |
| <b>SOURIAU</b> | <b>WWW.SOURIAU.COM</b>             |                            | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT         | <b>SOURIAU DRG N° 8D517X75PC-C</b> |                            | SHEET 2/2   |