



(B)
NOTES:
 1. MATERIAL: AS NOTED
 2. FINISH: AS NOTED
 3. ELECTRICAL:
 VOLTAGE: 600VAC
 CURRENT: 25A
 4. TEMP RATING: -20°C TO +90°C
 5. CSA CERTIFIED FILE: LR6837
 6. UL RECOGNIZED FILE: E46237
 7. ALL DIMS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE

MATERIAL NO.	ENGINEERING NO.
1300190018	43301

5	OVERMOLD	RUBBER	ORANGE
4	#6-32 BINDING HD SCREW-.50 LG	STEEL	NICKEL PLATE
3	#6-32 BINDING HD SCREW-.25 LG	Cu ALLOY	ZINC PLATE
2	SUPPORT PLATE	CRS	ZINC PLATE
1	SOCKET ASSEMBLY	Cu ALLOY	
ITEM	DESCRIPTION	MATERIAL	FINISH

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

FUNCTIONAL SYMBOLS	DIMENSION UNITS	SCALE	CURRENT REV DESC: ADDED NOTES					
$\nabla_A = 0$	INCH/MM	1:1	EC NO: 711366 DRWN: VHANDI 2021/12/22 CHK'D: RSTONE 2022/06/21 APPR: BWOODMAN 2022/06/24 INITIAL REVISION: DRWN: RSTONE 2013/01/21 APPR: JFMURPHY 2013/03/01					
$\nabla_E = 0$	GENERAL TOLERANCES (UNLESS SPECIFIED)					DOCUMENT NUMBER	DOC TYPE	DOC PART
$\nabla_S = 0$						SD-130019-004	PSD	001
DIVISIONAL SYMBOLS						REVISION		
	4 PLACES ±	MM						
	3 PLACES ±	INCH						
	2 PLACES ±							
	1 PLACE ±							
	0 PLACES ±							
	ANGULAR TOL ± 2.0°							
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING	SHEET NUMBER			
				B-SIZE	130019			
			MATERIAL NUMBER	CUSTOMER				
			SEE TABLE	GENERAL MARKET	1 OF 1			