

ATGBICS SFP-GE-LX-SM1270-BIDI-C network transceiver module Fiber optic 1250 Mbit/s

Brand : ATGBICS

Product code: SFP-GE-LX-SM1270-BIDI-C

Product name : SFP-GE-LX-SM1270-BIDI-C

Huawei Compatible Transceiver, SFP, 1000Base-BX-U, BiDi, Tx1270nm/Rx1330nm, 10km, SMF, DOM, Ind

ATGBICS SFP-GE-LX-SM1270-BIDI-C network transceiver module Fiber optic 1250 Mbit/s:

SFP-GE-LX-SM1270-BIDI 1000Base-BX SFP supports a distance of up to 10km over single mode fibre (SMF) using a wavelength of Tx1270nm/Rx1330nm via an LC connector. This product is suitable for rugged environments and can operate at temperatures between -40C to +85C. This bidirectional unit must be used with another transceiver or network appliance of complimenting wavelengths. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of Huawei SFP-GE-LX-SM1270-BIDI= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Power	
Maximum data transfer rate *1250 MbInterface type *SFPSingle-mode fiber (SMF) supported✓Multi-mode fiber (MMF) supported✓Fiber optic connectorLCSFP transceiver standardBX-UMaximum transfer distance10000 mTx wavelength (max)1270 nmRx wavelength (max)1330 nm	4	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W
		Operational conditions	
	LC	Minimum operating temperature Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H) Weight & dimensions	-40 °C 185 °C -40 - 85 °C -40 - 85 °C 0 - 95% 0 - 95%
	1	Width	13.4 mm
roduct colour Silver ousing material Metal	Depth Height Weight	56.5 mm 8.5 mm 15 g	
Plug and Play	4	Packaging data	
	✓ ✓ United Kingdom	Number of products included Package type	1 pc(s) Box
	Huawei	Technical details	
		Sustainability certificates	RoHS

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

×