

NEMA 5-15P  
PLUG

(1.68)

LENGTH "L"

(5.29)

NYLON COVER PLATE  
COLOR: YELLOW

NEMA 5-15  
SUPER-SAFEWAY  
WATERTITE  
DUAL-SIDED OUTLET BOX

POLYCARBONATE FLIP LIDS  
COLOR: YELLOW

GFCI PLUG 15A/120V  
RESET TYPE: MANUAL

(2.05)

12/3 SJOW/SJO CORD  
YELLOW

RUBBER BOX  
COLOR: YELLOW

(3.41)

(3.70)

(1.38)

(3.91)

**TECHNICAL**

LISTED: UL & CSA  
 RATED SUPPLY VOLTAGE: 120VAC  
 RATED CURRENT: UP TO 15 AMPS  
 RESET TYPE: MANUAL  
 OPERATING FREQUENCY: 60 Hz  
 TYPE: CLASS A  
 GROUND TRIP CURRENT: 4-6 mA  
 OVERLOAD CURRENT: 90 AMP 125 VAC  
 INSULATION VOLTAGE: 1,500 VRMS - 1 MINUTE  
 ENDURANCE OPERATIONS: 3000 OPERATIONS  
 GFCI ENCLOSURE: NEMA 3R

MATERIAL NUMBER	ENGINEERING NUMBER	LENGTH "L"
1301530080	15053W-2	2 FT. ± 1 IN.
1301530081	15053W-25	25 FT. ± 2 IN.
1301530086	15053W-50	50 FT. ± 4 IN.

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION									
FUNCTIONAL SYMBOLS	DIMENSION UNITS	SCALE	CURRENT REV DESC: NEW SALES DRAWING CREATED						
$\nabla_A = 0$	INCH	NTS	<b>molex</b> 15A GFCI PLUG W/DUAL DUPLEX PRODUCT CUSTOMER DRAWING DOCUMENT NUMBER: 1301530080 DOC TYPE: PSD DOC PART: 000 REVISION: A						
$\nabla_C = 0$	GENERAL TOLERANCES (UNLESS SPECIFIED)								
$\nabla_P = 0$	ANGULAR TOL ± °								
DIVISIONAL SYMBOLS	4 PLACES ±	3 PLACES ±	2 PLACES ±	1 PLACE ±	0 PLACES ±	EC NO: 686059	DRWN: PPURSUTANDEL	2021/11/16	
						CHK'D: DNGUYEN2	2021/12/01		
						APPR: HKNEELAND	2022/01/04		
						INITIAL REVISION:			
						DRWN: PPURSUTANDEL	2021/11/16		
						APPR: HKNEELAND	2022/01/04		
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	THIRD ANGLE PROJECTION	DRAWING	SERIES	MATERIAL NUMBER	CUSTOMER	SHEET NUMBER		
			C-SIZE	130153	SEE TABLE	GENERAL MARKET	1 OF 1		

DOCUMENT STATUS	P1	RELEASE DATE	2022/01/04	20:36:10
-----------------	----	--------------	------------	----------