


F611DY155M630C

Obsolete

F611, Film, Metallized Polyester, General Purpose, 1.5 uF, 20%, 630 VDC, 85°C, Lead Spacing = 22.5mm

FRONT VIEW



Click [here](#) for the 3D model.

Dimensions

- L 26mm -0.5mm
- H 24.5mm -0.5mm
- T 15.5mm -0.5mm

Dimensions

S 22.5mm +/-0.4mm
LL 4mm +2mm
F 0.8mm +/-0.05mm
G 0.5mm NOM

Packaging Specifications

Packaging Tray
Packaging Quantity 450

General Information

Series F611
Dielectric Metallized Polyester
Style Radial
Features Pulse
RoHS Yes
Lead Wire Leads
AEC-Q200 No
Miscellaneous The Rated Voltage Decreases 1.25%/C Between +85C And +105C (For +125C, Please Consult KEMET).

Specifications

Capacitance 1.5 uF
Capacitance Tolerance 20%
Voltage AC 220 VAC
Voltage DC 630 VDC, 472.5 VDC (105C)
Temperature Range -55/+105°C
Rated Temperature 85°C
Dissipation Factor 1.2% 1kHz
Insulation Resistance 6.667 GOhms
Max dV/dt 12 V/us
Inductance 6 nH

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 5/18/2023 - fdf59b07-8268-4fe8-b790-d0d5b85d900d
© 2006 - 2023 KEMET
Generated 5/18/2023 - fdf59b07-8268-4fe8-b790-d0d5b85d900d
© 2006 - 2023 KEMET