

Product data sheet

Characteristics

NSYZA2124G

Polyester glassreinf. plinth for encl. PLA(T)124
front opening IP44-IK10 RAL7035



Main

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or Component Type	Plinth
Anwendung	Multi-purpose
Nennmaße des Gehäuses	-
Device composition	Fixing elements 2 front panel 2 side part
Range compatibility	Thalassa PLA

Complementary

Fixing mode	By screws - on side parts
Color	Plinth Gray RAL 7035)
Height	7.87 in (200 mm)
Width	48.98 in (1244 mm)
Depth	13.78 in (350 mm)

Environment

IP degree of protection	IP44
IK degree of protection	IK10

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480777745
Nbr. of units in pkg.	1
Package weight(Lbs)	20.99 lb(US) (9.52 kg)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	6.30 in (16 cm)
Package 1 width	8.46 in (21.5 cm)
Package 1 Length	50.39 in (128 cm)

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration