

R60MI3150AA30M

Aliases (60MI3150AA30M)

R60, Film, Metallized Polyester, Automotive Grade, 0.15 uF, 20%, 400 VDC, 85°C, Lead Spacing = 15mm



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-----------------|
| L | 18mm +0.3mm |
| H | 11mm +0.1mm |
| T | 5mm +0.2mm |
| S | 15mm +/-0.4mm |
| LL | 4mm +1.5mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

| | |
|--------------------|-----------|
| Packaging | Bulk, Bag |
| Packaging Quantity | 2000 |

General Information

| | |
|----------------|---|
| Series | R60 |
| Dielectric | Metallized Polyester |
| Style | Radial |
| Features | Automotive Grade, DC Multipurpose Applications |
| RoHS | Yes |
| Lead | Cut |
| Qualifications | AEC-Q200 |
| AEC-Q200 | Yes |
| Miscellaneous | Upper Operating Temperature Of 125C Is Allowed For A Maximum Operating Time Of 1,000 Hours. Above 85C, DC And AC Voltage Derating Is 1.25%/C. |

Specifications

| | |
|-----------------------|------------|
| Capacitance | 0.15 uF |
| Capacitance Tolerance | 20% |
| Voltage AC | 200 VAC |
| Voltage DC | 400 VDC |
| Temperature Range | -55/+105°C |
| Rated Temperature | 85°C |
| Dissipation Factor | 1% 1kHz |
| Insulation Resistance | 30 GOhms |
| Max dV/dt | 20 V/us |
| Inductance | 10 nH |