



Main

Range	ClimaSys
Product name	ClimaSys CV
Product or Component Type	Fanbox without grille and filter
Application	Outdoor heavy duty
Range compatibility	PHD S3HD SFHD
Flow rate	Free flow rate 145297.23 Gal/hr(US) (550 m3/h) 50 Hz 145297.23 Gal/hr(US) (550 m3/h) 60 Hz
[Us] rated supply voltage	115 V AC +/- 10 %
Input voltage	115 V AC 50/60 Hz
Certification	CE UL UL 508 A CSA CSA C22.2 Ecodesign directive 2009/125/EC

Complementary

Absorbed power	78...102 W
Line Rated Current	0.7...0.8 A 50 Hz
Noise level < at	60 dB
Bearing type	Ball
Height	External 8.78 in (223 mm)
Width	External 8.78 in (223 mm)
Depth	External 3.54 in (90 mm)
Net Weight	3.75 lb(US) (1.7 kg)
Color	Dark grey RAL 7016)
Ambient Air Temperature for Operation	-40...158 °F (-40...70 °C)
Ambient Air Temperature for Storage	-40...176 °F (-40...80 °C)
Maximum pressure	300 Pa flow rate 0 m³/h
Connections - Terminals	Spring clamp terminal
IP degree of protection	Grid IP55 IP44
Device composition	1 fanbox 4 screw
Condition of use	Overfrequent filter replacement should be avoided Flow rates depends on the work point, see ProClima software Surrounding environment must be relatively clean Filter must be cleaned and replaced regularly Outside temperature must be 5 °C lower than inside temperature

Ordering and shipping details

Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480678776
Nbr. of units in pkg.	1
Package weight(Lbs)	4.41 lb(US) (2.0 kg)
Returnability	No
Country of origin	ES

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.57 in (4 cm)
Package 1 width	5.91 in (15 cm)
Package 1 Length	5.91 in (15 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information