



R0.5 MAX. OR CORNER RELIEF (TYP) **RECOMMENDED MOUNTING CUTOUT**
SCALE 2:1

NOTES:

1. MATERIALS:
 ADAPTER BODY - POLYETHERIMIDE (BLACK)
 FLAMMABILITY: UL94 V-0
 SPRING CLIP - STAINLESS STEEL
 DUST PLUGS - POLYCARBONATE
 SURFACE RESISTIVITY: <1E12 ohm/sq
 TML: <1%
 FLAMMABILITY: UL94 V-0

2. KEY ORIENTATION - OPPOSED

SYMBOLS										THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION															
▽ = 0		mm		3:1		CURRENT REV DESC:		molex		EC NO: 615471		2019/04/11		MTP ADAPTER, REDUCED FLANGE		PRODUCT CUSTOMER DRAWING		DOCUMENT NUMBER		DOC TYPE		DOC PART		REVISION	
▽ = 0		GENERAL TOLERANCES (UNLESS SPECIFIED)		ANGULAR TOL ± 0.5°		DRWN: IGUMIN		2019/04/11		CHK'D: GGENCHANOK		2019/04/11		SD-106181-0007		PSD		001		C1					
▽ = 0		4 PLACES ±		3 PLACES ±		2 PLACES ±		1 PLACE ±		0 PLACES ±		INITIAL REVISION:		DRWN: KPEVZNER		2006/07/10		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER		1 OF 1	
▽ = 0		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		106181		1061810007													