

USB 3.0 SuperSpeed Device Cable (A to Micro-B M/M) Black, 3-ft.

MODEL NUMBER: U326-003-BK



Connects a USB3.0 enabled computer to a USB3.0 peripheral with Micro B type connector

Description

Tripp Lite's SuperSpeed USB 3.0 cable brings significant performance enhancements to the ubiquitous USB standard, while remaining compatible with the billions of USB enabled devices currently deployed in the market. SuperSpeed USB will deliver 10x the data transfer rate of Hi-Speed USB, up to 5Gbps, as well as improved power efficiency. USB 3.0 utilizes a bi-directional data interface rather than USB 2.0's half-duplex arrangement, where data can only flow in one direction at a time, giving a ten-fold increase in theoretical bandwidth.

Features

- 3-ft. SuperSpeed USB 3.0 A Male to Micro B Male Black
- SuperSpeed USB is 10 times faster than Hi-Speed USB, with transfer rates up to 5 Gbps.
- Sync-N-Go technology minimizes user wait-time.
- Provides Optimized Power Efficiency...No device polling and lower active and idle power requirements.
- Backwards compatible with USB 2.0. Devices interoperate with USB 2.0 platforms. Hosts support USB 2.0 legacy devices.

Specifications

OVERVIEW	
UPC Code	037332183170
INPUT	
Cable Length (ft.)	3

Highlights

- 3-ft. SuperSpeed USB 3.0 A to Micro B Cable
- 10 times faster than USB 2.0, with transfer rates up to 5 Gbps

System Requirements

 Computers and Peripherals with USB 3.0 capabilities

Package Includes

3-ft. SuperSpeed USB 3.0 A
 Male to Micro B Male Device
 Cable - Black





Cable Length (m)	0.9	
Cable Length (in.)	36	
PHYSICAL		
Wire Gauge (AWG)	28/28/24	
Shipping Dimensions (hwd / in.)	0.25 x 5.60 x 8.90	
Shipping Dimensions (hwd / cm)	0.64 x 14.22 x 22.61	
Shipping Weight (lbs.)	0.10	
Shipping Weight (kg)	0.05	
Material of Construction	PVC	
Color	Black	
Cable Outer Diameter (OD)	5.5MM	
Cable Jacket Rating	VW-1	
ENVIRONMENTAL		
Operating Temperature Range	14 to 140 F (-10 to 60 C)	
Storage Temperature Range	-4 to 185 F (-20 to 85 C)	
Relative Humidity	10% to 85%, Non-Condensing	
,	The transfer of the transfer o	
CONNECTIONS		
Side A - Connector 1	USB 3.0 A (MALE)	
Side B - Connector 1	USB 3.0 MICRO-B (MALE)	
Connector Plating	Nickel	
Contact Plating	Gold	
FEATURES & SPECIFICATIONS		
USB Specification	USB 3.0 (up to 5 Gbps)	
Technology	USB 3.0 (SuperSpeed); USB	
CERTIFICATIONS		
Certifications	Tested to CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2019 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

https://www.tripplite.com/products/product-certification-agencies