



Recommended  
Cable Stripping Dim's

- NOTES: Finish (Plating Thickness in Micro-inches)
1. Brass
  2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick
  3. Gold Pl. 5 Min Thick over Copper Pl. 50 Min. Thick over Copper Pl. 50 Min Thick
  4. Teflon
  5. Phosphor Bronze

Crimped Ferrule  
Hex. Crimp Size .429 (10.9)  
Crimped Contact Pin  
Hex. Crimp Size .118 (3.0)

RoHS Compliant

8	Ferrule	Note 1	Note 2	1		Dimensions are in Inches Unless Otherwise Specified Tolerances 0.5-6 = ±0.2 6-30 = ±0.4 30-120 = ±0.6 120-315 = ±1 315-1000 = ±1.6 1000-2000 = ±2.4	Part No.		<h1>NTE Electronics</h1>
7	Contact Pin	Note 1	Note 3	1	Approved		Date	Title	
6	Retainer Ring	Note 5	Natural	1	Checked		Date	(For LMR400, Belden 9913 Cable)	
5	Gasket	Silicone	Red	1	Drawn		Date	Drawing No.	
4	Insulator	Note 4	Natural	1			12-2-2010	06-N001	
3	Barrel	Note 1	Note 2	1			File No.		
2	Body	Note 1	Note 2	1					
1	Shell	Note 1	Note 2	1					
No.	Description	Material	Finish	Q'ty	Drawing No.	Scale	2.5/1	Issue	A1

**NTE Electronics**

Title  
N Crimp Plug  
(For LMR400, Belden 9913 Cable)

Drawing No. 06-N001

File No.

A

A

F

F

E

E

D

D

C

C

B

B