

ITEM	PART#	DESCRIPTION	QTY	UOM
A	436450300	MicroFit 3.0 Receptacle Sgl Row 3Ckt	1	PC
B	430300040	MicroFit 3.0 F Crp Term Chn 30Au 18	3	PC
C	--	PAPER PRINTED PAPER WHITE	1	PC

FROM	TO	DESCRIPTION	COLOR
A1	--	1X18AWG DISC SR-PVC BK UL10002	BLACK
A2	--	1X18AWG DISC SR-PVC BK UL10002	BLACK
A3	--	1X18AWG DISC SR-PVC BK UL10002	BLACK




TABLE			
PART NUMBER	L1	L2	TITLE
2147512031	150±8	63 REF	MICROFIT 3.0 SR R-S 3CKT 150 MM Au
2147512032	300±10	138 REF	MICROFIT 3.0 SR R-S 3CKT 300 MM Au
2147512033	600±10	288 REF	MICROFIT 3.0 SR R-S 3CKT 600 MM Au

NOTES

1. Connector view shown is from mating side.
2. Free ends must be stripped, twisted & tinned. The length of tinning is 5±1mm. Tinning dia must be 1.55mm Max.
3. Label text must be 2mm max. in height with Arial font.
4. Label must be wrapped in Flag type on a single cable.

PRE-RELEASE
REFERENCE
USE ONLY

MOLEX P/N
MOLEX
BATCH WK/YR
DETAIL A

REVISION			
DATE	REV	DESCRIPTION	CHANGER
2020/02/29	A	INITIAL RELEASE	ARAJU

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION											
SYMBOLS		DIMENSION UNITS		SCALE		CURRENT REV DESC:					
∇ = 0	mm	NTS		EC NO: 637489 DRWN: ARAJU 2020/02/29 CHK'D: RDESAI01 2020/05/14 APPR: RDESAI01 2020/05/14 INITIAL REVISION: DRWN: ARAJU 2020/02/29 APPR: RDESAI01 2020/05/14							
∇ = 0	GENERAL TOLERANCES (UNLESS SPECIFIED)										
∇ = 0	ANGULAR TOL ± °										
∇ = 0	4 PLACES	±									
∇ = 0	3 PLACES	±									
∇ = 0	2 PLACES	±									
∇ = 0	1 PLACE	±									
∇ = 0	0 PLACES	±									
∇ = 0	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS										
∇ = 0	THIRD ANGLE PROJECTION		DRAWING							SERIES	
		A4-SIZE		214751		2147512031		PSD	000	A	
RELEASE STATUS		P1	RELEASE DATE		2020/05/14 03:37:05		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER
							SEE TABLE		GENERAL MARKET		1 OF 1