

## Specification Sheet

Part Number: T250M0X2



Heavy Duty Cable Tie, 22.3" Long, UL Rated, 250lb Tensile Strength, PA66, Black, 25/pkg

|                     |   |
|---------------------|---|
| Article Number      | 111-25001   |
| Type                | T250M   |
| Color               | Black (BK)  |
| Features & Benefits | <ul style="list-style-type: none"><li>•Engineered and manufactured for maximum performance and quality.</li><li>•Made from 100% high-quality plastic to ensure efficient recycling.</li><li>•Inside serration for a strong grip onto bundles.</li><li>•Easy application either manually or with a tensioning tool.</li><li>•Bent tail allows for simpler insertion.</li></ul> |
| Quantity Per        | bag   |

**Product Description**

These cable ties offer a high minimum tensile strength and have a buckle feature which allows the end of the cable tie to be tucked away if necessary. The buckle also snaps into HellermannTyton lashing tie mounts (LTM.) T-Series Cable Ties feature inside serrations to provide a positive hold on wire and cable bundles. The head design guarantees high tensile strength and a low insertion force. The bent tail design allows quick and simple installations by hand. For high-volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description**

Heavy Duty Cable Tie, 22.3" Long, UL Rated, 250lb Tensile Strength, PA66, Black, 25/pkg

**Global Part Name**

T250M-PA66-BK

**Minimum Tensile Strength (Imperial)**

250.0

**Minimum Tensile Strength (Metric)**

1115.0

**Length L (Imperial)**

22.3

**Length L (Metric)**

565.3

**Identification Plate Position**

none

**Releasable Closure**

No

**Tie Closure**

plastic pawl

**Variant**

Inside Serrated

**Width W (Imperial)**

0.49

**Width W (Metric)**

12.4

**Bundle Diameter Min (Imperial)**

0.47

**Bundle Diameter Min (Metric)** 12.0

**Bundle Diameter Max (Imperial)** 5.9

**Bundle Diameter Max (Metric)** 150.0

**Thickness T (Metric)** 1.9

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL 94 V2

**Halogen free** Yes

**Operating Temperature (Metric)** -40°F to +185°F (-40°C to +85°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** UL | ANSI/UL 746B UL | ANSI/UL 1565 UL | ANSI/UL 62275

**UL Recognized (US)** Yes

**UL Recognized (US and Canada)** Yes

**Package Quantity(Imperial)** 25

**Package Quantity (Metric)** 25

**Customs Number** 3926909988

**Content Unit(BMEcat)** pcs.

**Weight (Metric)** 12