

C9TS6MD6137AARX

C9T, Film, Metallized Polypropylene, AC Filter, 137 uF, -5/+10%, 440 VAC



Click [here](#) for the 3D model.

Dimensions

D 85mm +/-0.5mm

L 280mm +/-2mm

Packaging Specifications

Mounting Bolt - M12x16

Packaging Bulk, Bag

Packaging Specifications

Packaging Quantity 9

General Information

Series	C9T
Dielectric	Metallized Polypropylene
Style	Can
Features	Three Phase PFC
RoHS	Yes
Lead	Quick Connect
Qualifications	VDE
AEC-Q200	No
Component Weight	1694 g
Miscellaneous	Q = 25 kvar. Operating Freq. = 50 Hz.

Specifications

Capacitance	137 uF
Capacitance Tolerance	-5/+10%
Voltage AC	440 VAC
Temperature Range	-25/+55°C
Rated Temperature	55°C
Max dV/dt	30 V/us
Ripple Current	43 Amps

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.

Generated 5/18/2023 - d0e90c8c-3a0e-4a46-b1ef-a93c3101b394

© 2006 - 2023 KEMET

Generated 5/18/2023 - d0e90c8c-3a0e-4a46-b1ef-a93c3101b394

© 2006 - 2023 KEMET