	Ξ Ω Π		0		
4					4
ω			LAYOUT SHOWN AS EXAMPL	E	3
	Keying Shown as example				
	CHARACTERISTICS Connector dimension -Standard : Based on MIL-DTL-38999 Series III Dim Nominal				
	Shell Material: AluminiumØS29.4 Max-Shell Plating: Olive drab CadmiumZ31 Max-Insulator: Thermoplastic-Contacts: Copper Alloy-Seals & Grommet: Silicon Elastomer	SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)			
2	-Contact Plating : Gold over copper Alloy 0.8μm minimum -Durability : 500 Mating cycles -Delivered without Souriau contacts	FR Not Listed 2 PN: 8D513W26PDL 2			
	-Temperature Range -65°C to +175°C	A 19-10-2016	First Release		
	-Salt Spray : 500 hours -Mass : 20.05 g ± 10%	ISS DATE	Latest modification - by	MOD N	v.
	. 20.05 8 - 10/0	Designed By:	Date:	CUSTOMER DRAWING	
		TITLE Aluminium I			
<u> </u>	BASIC SERIES: 8D 5 - 13 W 26 P D L SHELL TYPE : Plug with RFI Shielding - 13 W 26 P D L	SCALE -	General linear Tolerances:	NPRDS / PROJECT 859	
	CONTACT TYPE : Standard Crimp Contact SHELL SIZE : 13 CONTACT TYPE : PIN(500 Matings)	SOURIAU WWW.SOURIAU.COM This document is the property of SOURIAU it must not be reproduced or communicated without permission			
	PLATING : W = Olive drab Cadmium CONTACT LAYOUT : 13-26	-			
		A3	8D513W26PI		
	H G F E	D		B A	

r	Ŧ	G	г П	m	U	0
		Contact Layout				
4		26				
		2#12 6#22D	l			
ω	Ctc A B C D E F 1 2	X Y 0 3.47 2.47 4.34 2.47 -4.34 0 -3.47 -2.47 -4.34 -2.47 -4.34 3.25 0 -3.25 0				
	-					SOURIAU shall not be liable for an due to a use of the Products wh the Specifications issued by either of (professional recommendat
N						
_					A 19-10-20 ISS DATE Designed By:	PN: 8D513W
					TITLE	Alumin General linear
_					NA	Tolerances:
					FORMAT A3	WWW.SOURIAU.C SOURIAU 8D513W2
L	Н	G	F	E	D	C

