


5502G1 Multi-Conductor - Water-Blocked for Indoor/Outdoor Use

For more Information
please call

1-800-Belden1



General Description:

Rated-CM, 1-22 AWG tinned copper pair with PVC insulation and a Beldfoil shield, 2-22 AWG tinned copper conductors with PVC insulation, Overall water resistant tape and PVC jacket with ripcord

Physical Characteristics (Overall)

Conductor

AWG:

# Conductors	# Pairs	AWG	Stranding	Conductor Material
	1	22	7x30	TC - Tinned Copper
2		22	7x30	TC - Tinned Copper

Total Number of Conductors: 4

Insulation

Insulation Material:

Insulation Material	Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.254

Inner Shield

Inner Shield Material:

Inner Shield Trade Name	Type	Inner Shield Material	Coverage (%)
Beldfoil®	Tape	Aluminum Foil-Polyester Tape	100

Inner Shield Drain Wire AWG:

AWG	Stranding	Conductor Material
24	7x32	TC - Tinned Copper

Inner Shield Waterblocking Tape: Non-woven

Outer Shield

Outer Shield Material:

Outer Shield Material
Unshielded

Outer Shield Waterblocking Tape: Yes

Outer Jacket

Outer Jacket Material:

Outer Jacket Material	Nom. Wall Thickness (mm)
PVC - Polyvinyl Chloride	0.635

Outer Jacket Ripcord: Yes

Overall Cable

Overall Cabling Color Code Chart:

Number	Color	Group/Cond. Color
1	Black and Red	Shielded Pair
2	White	Conductor
3	Green	Conductor

Overall Nominal Diameter: 5.944 mm

Pair

Pair Lay Length & Direction:

Lay Length (mm)

38.1

Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +105°C
Bulk Cable Weight:	36.312 Kg/Km
Max. Recommended Pulling Tension:	161.914 N
Min. Bend Radius/Minor Axis:	60.325 mm

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

NEC/(UL) Specification:	CM
CEC/C(UL) Specification:	CM
EU Directive 2011/65/EU (ROHS II):	Yes
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	10/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flame Test

UL Flame Test:	UL1685 UL Loading
C(UL) Flame Test:	FT1

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)

Nom. Inductance:

Inductance (µH/m)
0.59058

Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)
146.005

Nom. Capacitance Cond. to Other Conductor & Shield:

Capacitance (pF/m)
262.808

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)
53.8084

Maximum Conductor DC Resistance:

DCR @ 20°C (Ohm/100 m)
53.8084

Max. Operating Voltage - UL:

Voltage
300 V RMS

Max. Recommended Current:

Current
2.2 Amps per conductor @ 25°C

5502G1 Multi-Conductor - Water-Blocked for Indoor/Outdoor Use

Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
5502G1 008Z1000	1,000 FT	29.000 LB	GRAY		1 FSPR + 2 #22 S-R PVC PVC
5502G1 0081000	1,000 FT	29.000 LB	GRAY	C	1 FS PR + 2 #22 S-R PVC PVC
5502G1 008500	500 FT	14.000 LB	GRAY		1 FS PR + 2 #22 S-R PVC PVC

Notes:

C = CRATE REEL PUT-UP.

Revision Number: 2 Revision Date: 03-13-2013

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).