

Specification Sheet

Part Number: 558-00380



Adhesive Labels, Banded Color Continuous Roll, 2.0" x 250', UV Stable PET, Orange/White, 250 ft/roll

Article Number	558-00380
Type	HT2OE50250UV
Color	Orange (OG)
Features & Benefits	<ul style="list-style-type: none">• Continuous Colored Signal Panel labels come with yellow or orange stripes for easy printing of caution and warning labels.• Continuous labels allow for designing and cutting labels to any length.• Various widths are available so that a wide variety of sign sizes can be customized and produced on demand.
Quantity Per	roll

Product Description

The Pre-printed colored header vinyl rolls can be used to design signs that conform to Occupational Safety and Hazard Association (OSHA) and American National Standards Institute (ANSI) requirements for Warning and Caution Signs and markers. All can be designed, printed and cut to length in Tagprint Pro and any HellermannTyton thermal transfer printing system.

Short Description	Adhesive Labels, Banded Color Continuous Roll, 2.0" x 250', UV Stable PET, Orange/White, 250 ft/roll
Global Part Name	HT2OE50250UV-840/926-OG
Technical Description	Banded Continuous Colored Signal Panel Roll, 2.0" X 250', UV Stable, Orange/White
Length L (Imperial)	250.0
Length L (Metric)	76.2
Variant	3.2mil, 50lb bleached kraft paper
Width W (Imperial)	2.0
Width W (Metric)	50.8
Thickness T (Metric)	64.0
Width of Liner (Metric)	50.8
Width of Liner (imperial)	2.0
Material	Type 840/926, Polyester (PET), UV stable, clear Polyester laminate
Material Shortcut	840/926
Adhesive	Acrylic

Halogen free No

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Operating Temperature (Metric) -40°F to +302°F (-40°C to +150°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB CSA 66956 NEC2014 NEC2011 IFC 2012 UL 969 ANSI Standard Z535.4

UL Recognized (US) Yes

Package Quantity(Imperial) 250

Package Quantity (Metric) 76.20

Customs Number 3919102055

Content Unit(BMEcat) reel

Labels per Column 1

Labels per Row 1

Weight (Metric) 0.34

Weight (Imperial) 0.749

