

## LDEDA2180MA0N00

Aliases (DEDA2180MA0N00)

LDE, Film, Metallized PEN Stacked, Automotive Grade, 0.018 uF, 20%, 40 VAC, 63 VDC, 125°C, 1206, 1.1mm



Click [here](#) for the 3D model.

### Dimensions

|           |                   |
|-----------|-------------------|
| Chip Size | 1206              |
| L         | 3.3mm +0.3/-0.1mm |
| W         | 1.7mm +/-0.2mm    |
| T         | 1.1mm MAX         |
| B         | 0.4mm +0.5/-0.3mm |

### Packaging Specifications

|                    |      |
|--------------------|------|
| Packaging          | T&R  |
| Packaging Quantity | 3000 |

### General Information

|                |                        |
|----------------|------------------------|
| Series         | LDE                    |
| Dielectric     | Metallized PEN Stacked |
| Style          | SMD Chip               |
| Features       | Automotive Grade       |
| RoHS           | Yes                    |
| Qualifications | AEC-Q200               |
| AEC-Q200       | Yes                    |
| Shelf Life     | 104 Weeks              |
| MSL            | 3                      |

### Specifications

|                       |            |
|-----------------------|------------|
| Capacitance           | 0.018 uF   |
| Capacitance Tolerance | 20%        |
| Voltage AC            | 40 VAC     |
| Voltage DC            | 63 VDC     |
| Temperature Range     | -55/+125°C |
| Rated Temperature     | 125°C      |
| Dissipation Factor    | 0.8% 1kHz  |
| Insulation Resistance | 1 GOhms    |
| Max dV/dt             | 100 V/us   |